

SAE-J336

ADOPTION NOTICE

SAE-J336, "Truck Cab Interior, Sound Level for," was adopted on October 3, 1994, for use by the Department of Defense (DoD). Proposed changes by DoD activities must be submitted to the DoD Adopting Activity: WR-ALC/TILBA, 255 Second Street, Robins AFB GA 31098-1637. DoD activities may obtain copies of this standard from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094. The private sector and other Government agencies may purchase copies from the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.

Custodians:  
 Army - MI  
 Navy - SA  
 Air Force - 84

Adopting Activity  
 Air Force - 84

SAENORM.COM : Click to view the full PDF of J336-199415

AREA HFAC

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

**SAE** The Engineering Society  
For Advancing Mobility  
Land Sea Air and Space®

A Product of the  
Cooperative Engineering Program

**SAE J336 OCT88**

**Sound Level for  
Truck Cab Interior**

SAE Recommended Practice  
Revised October 1988

SAENORM.COM : Click to view the full PDF of J336-198810

Submitted for Recognition as  
an National Standard

SAENORM.COM : Click to view the full PDF of j336 \_ 198810

No part of this publication may be reproduced in any form,  
in an electronic retrieval system or otherwise, without the  
prior written permission of the publisher.

**SAE** The Engineering Society  
For Advancing Mobility  
Land Sea Air and Space®

400 COMMONWEALTH DRIVE, WARRENDALE, PA 15096

## HIGHWAY VEHICLE PRACTICE

SAE J336

Issued June 1968  
Revised October 1988

Superseding J336 FEB87

Submitted for recognition as an American National Standard

### Ø SOUND LEVEL FOR TRUCK CAB INTERIOR

#### 1. INTRODUCTION:

This SAE Recommended Practice describes the equipment and procedure for determining the truck cab interior sound level over the upper half of the engine speed range. This practice applies to motor trucks and truck-tractors and does not include construction and industrial machinery.

#### 2. INSTRUMENTATION:

The following instrumentation shall be used:

- 2.1 A sound level meter which meets the Type 1 or S1A requirements of American National Standard, Specification for Sound Level Meters, S1.4-1983.
  - 2.1.1 As an alternative to making direct measurements using a sound level meter, a microphone or sound level meter may be used with a data recorder and/or a graphic level recorder or other indicating instrument, provided that the system used meets the requirements of SAE J184 AUG87, Qualifying a Sound Data Acquisition System.
- 2.2 A sound level calibrator accurate within  $\pm 0.5$  dB. (See 4.2.3.)
- 2.3 An engine-speed tachometer accurate within  $\pm 2\%$  of full scale.
- 2.4 An anemometer accurate to  $\pm 10\%$  at 19 km/h (12 mph).

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

### 3. TEST PROCEDURE:

The following procedure is to be used for the purpose of this SAE Recommended Practice:

- 3.1 Establish a seat reference point at the intersection of the tangent lines to the predominant surfaces of the undeflected cushion and backrest at the lateral center of the seat (or intended operator location). Adjust the seat to the midpoint of its horizontal and vertical travel.

Locate the microphone, oriented vertically upward, at a point 740 mm (29 in) vertically above the seat reference point and 250 mm (10 in) laterally to the right (to the left for right-hand drive vehicles) of the seat reference point.

Position the driver so that his ear is reasonably aligned with, and approximately 150 mm (6 in) laterally from, the microphone. Seat adjustment may be made to meet this provision.

- 3.2 Sound level tests may be conducted with or without a trailer or body on the vehicle. The configuration shall be recorded.
- 3.3 The engine coolant shall be within the manufacturer's recommended operating temperature range during testing.
- 3.4 Vehicle windows and vents shall be in the fully closed position with all accessories "off."
- 3.5 The tests shall be conducted on a smooth, dry concrete or asphalt road surface. No large sound-reflecting surfaces should be within 15 m (50 ft) of the test vehicle. Wind speed should not exceed 19 km/h (12 mph). The test personnel should be aware that the direction of the wind relative to the vehicle may have an influence on the measurement.
- 3.6 Select a transmission and/or axle gear ratio so that approximately 80 km/h (50 mph) is obtained at rated engine speed. "Rated engine speed" is defined as the engine speed at which the engine delivers "Rated Power", as defined in SAE J1349 JUN85, Engine Power Test Code - Spark Ignition and Diesel, as specified by the engine manufacturer.
- 3.7 For each test run, accelerate the vehicle in the selected gear ratio of paragraph 3.6 at wide-open throttle from a beginning engine speed of one-half rated engine speed up to rated engine speed. A minimum of four test runs shall be made.

3.8 The applicable reading shall be the highest A-weighted sound level, observed during each test run of paragraph 3.7. The meter shall be set for "fast exponential-time-averaging" for these measurements. The test run shall be repeated until four sound level readings are obtained with a total range of 2 dB, or less. The reported sound level shall be the average of the four highest readings within a total range of 2 dB, or less. The observer is cautioned to rerun a test run if unrelated peaks should occur because of sounds that are not caused by the vehicle.

3.8.1 If a data-recording system is used, make recordings during each test run. Record a calibration signal of known acoustic level immediately prior to, or following, each sequence of test recordings. For analysis of the test run recordings, use the calibration signal to establish playback gain and thus calibrate the analysis system. Set the level indicating instrument for "fast exponential-time-averaging" or equivalent for analysis of the recorded data.

#### 4. GENERAL COMMENTS:

4.1 It is strongly recommended that technically qualified personnel select the equipment, and that tests are conducted only by persons trained in the current techniques of sound measurement.

4.2 Proper use of all test instrumentation is essential to obtain valid measurements. Operating manuals or other literature furnished by the instrument manufacturer should be referred to for both recommended operation of the instrument and precautions to be observed. Specific items to be considered are:

4.2.1 The effects of ambient weather conditions on the performance of all instruments (that is, temperature, humidity, and barometric pressure).

4.2.2 Proper signal levels, terminating impedances, and cable lengths on multi-instrument measurement systems.

4.2.3 Proper acoustical calibration procedure, to include the influence of extension cables, etc. Field calibration shall be made immediately before and after each test sequence. Internal calibration means is acceptable for field use, provided the external calibration is accomplished immediately before or after field use.

4.2.4 The microphone shall be supported in such a manner that mechanical vibration will not influence the sound level measurements.

4.3 The sound level of a diesel engine may be dependent on the fuel's cetane level. A diesel fuel with a cetane number between 42-50 is recommended. For gasoline-fueled engines, a fuel grade consistent with the engine manufacturer's recommendation should be used.

- 4.4 It is recommended that the ambient temperature be reported with the test results because ambient temperature may influence the measured sound level. If the relationship between the measured sound level and the ambient temperature is known, and the test results are to be corrected to a reference ambient temperature, 25°C (77°F) is recommended as the reference ambient temperature. If the test result is corrected, it must be reported as a "corrected sound level" at the reference ambient temperature of 25°C (77°F).
- 4.5 For repeated development tests where the relative change in sound level is a desired quantity, the position of the microphone in the truck cab, and the position of the driver relative to the microphone (see 3.1) should remain constant.
- 4.6 Road surfaces, such as those with concrete joints, which add significant noise, should be avoided.
5. REFERENCES:
- 5.1 SAE J184 AUG87, Qualifying a Sound Data Acquisition System.
- 5.2 SAE J1349 JUN85, Engine Power Test Code - Spark Ignition and Diesel.
- 5.3 ANSI S1.4-1983, Specifications for Sound Level Meters.
- 5.4 ISO 5128 Acoustics, Measurement of Noise Inside Motor Vehicle.
- 5.5 Title 49 CFR 393.94, Vehicle Interior Noise Levels.

The phi (Ø) symbol is for the convenience of the user in locating areas where technical revisions have been made to the previous issue of the report. If the symbol is next to the report title, it indicates a complete revision of the report.

J336 OCT88

RATIONALE:

In June, 1968, the Vehicle Sound Level Committee approved the original test procedure for measuring the interior sound level of truck cabs. Interior sound levels were recognized as a truck parameter that needed to be quantified.

The concept of this test procedure is to keep the test simple and not time-consuming, but still maintain repeatability and accuracy in the test result. The result is intended to be a single number that is a measure of the highest noise level over the engine speed range typically used, with the engine at full power under acceleration conditions that are not far from real-world operation.

The sound level instrumentation specified was selected in accordance with ANSI S1.4 and SAE J184 requirements. The anemometer and tachometer instrumentation was specified with what was felt to be reasonable accuracy consistent with other SAE noise test procedures.

The vehicle operation is intended to be straightforward and repeatable. Gear selection is intended to represent on-highway acceleration conditions. Full throttle acceleration tests are used to produce a maximum sound level condition in the truck cab. However, a search of all operating conditions that could produce the maximum sound level is not what is desired here. The test site, ambient test conditions and general comments are intended to improve repeatability, but still allow flexibility. Cautions are given for several areas (wind direction and road surface) where the influence on results cannot be defined yet. To improve repeatability, controls on wind speed, microphone location, driver-to-microphone location, engine coolant temperature, fuel, window position, and vent position are specified.

A-weighted sound levels are specified as the measured result. This was selected to satisfy the needs of the industry and yet keep the data analysis simple. The resultant sound level is the average of at least four test runs. This requirement will improve measurement repeatability.

The effect of ambient temperature on the sound level result cannot be predicted by a general relationship for all vehicles. However, the effect needs to be recognized because for some vehicles, typically with air-to-air intercooled engines, the repeatability of the test would be unacceptable as ambient temperature varied. The attached graph demonstrates a 3 dB(A) change in sound level for a 33°C (60°F) change in ambient temperature for repeated tests on the same vehicle. Recording ambient temperature with the test data will aid the future understanding of the effects of ambient temperature. A reference temperature is recommended so that everyone will correct the same sound level data to the same result. A reference temperature of 25°C (77°F) was selected to be consistent with SAE engine performance test procedures and with engine exhaust emission test procedures. The establishment of a relationship between sound level and ambient temperature, for a specific vehicle, cannot be accomplished in this procedure, and is therefor left to the individual correcting the data.