

A Product of the
Cooperative Engineering Program

SAE J385 APR86

**Motor Vehicle Seat
Belt Anchorages —
Performance
Requirements**

SAE Standard
Reaffirmed April 1986

SAENORM.COM : Click to view the full PDF of J385_198604

**S. A. E.
LIBRARY**

Submitted for Recognition as
an American National Standard



*This standard is indexed
in the Standards Search Database*

SAENORM.COM : Click to view the full PDF of j385 - 198604

**No part of this publication may be reproduced in any form,
in an electronic retrieval system or otherwise, without the
prior written permission of the publisher.**

Copyright 1986 Society of Automotive Engineers, Inc.

RATIONALE:

SAE J787b has been discontinued and replaced by this report, SAE J383, and SAE J384.

RELATIONSHIP OF SAE STANDARD TO ISO STANDARD:

Not applicable.

REFERENCE SECTION:

SAE J383, Motor Vehicle Seat Belt Anchorages--Design Recommendations

SAE J384, Motor Vehicle Seat Belt Anchorages--Test Procedure

SAE J787, Motor Vehicle Seat Belt Anchorage

APPLICATION:

This SAE Recommended Practice specifies performance requirements for either static or dynamic testing of seat belt anchorages attached to vehicle structure or to the seat assemblies as installed in the motor vehicle.

COMMITTEE COMPOSITION:

DEVELOPED BY THE RESTRAINT SYSTEMS SUBCOMMITTEE:

- R. A. Strasser, Ford Motor Company, Dearborn, MI - Chairman
- J. J. Cantalupo, Ann Arbor, MI - Vice Chairman
- L. L. Baker, Brighton, MI
- D. M. Blaisdell, Severy, Inc., El Segundo, CA
- R. Brocklehurst, B. L. Technology Ltd., England
- R. F. Chandler, Federal Aviation Administration, Oklahoma City, OK
- C. G. Dewey, Alliance of American Insurers, Schaumburg, IL
- R. Gulette, Irvin Industries, Inc., Rochester, MI
- H. L. Hanson, American Motors Corp., Southfield, MI
- G. M. Hespeler, Daimler-Benz A.G., Montvale, NJ
- H. G. Johannessen, Omni-Safe, Inc., Rochester, MI
- W. A. Kohn, American Safety Equip. Corp., Troy, MI
- E. R. McKenna, Algonac, MI
- R. J. Neff, Phoenix Trimming Co., Northbrook, IL
- V. T. Newton, Chrysler Corporation, Detroit, MI
- J. L. Pearson, General Motors Corp., Warren, MI
- F. D. Pepe, U.S. Testing Co., Inc., Hoboken, NJ
- K. R. Rosendahl, Chrysler Corporation, Highland Park, MI
- H. G. Rouleau, Chrysler Corporation, Detroit, MI
- L. W. Schneider, University of Michigan, Ann Arbor, MI
- D. M. Severy, Severy, Inc., El Segundo, CA
- G. Smith, Bloomfield Hills, MI
- W. E. Smith, Nat'l. Hwy. Traffic Saf. Admin., Washington, DC
- R. G. Snyder, Univ. of Michigan, Ann Arbor, MI
- H. S. Willson, Dexter, MI
- G. Wize, General Motors Corporation, Warren, MI

SPONSORED BY THE SAE BODY ENGINEERING COMMITTEE:

E. G. Zipp, Chrysler Corp., Detroit, MI - Chairman
D. W. Ableson, General Motors Corporation, Pontiac, MI - Sponsor
D. G. Anticuar, Chrysler Corporation, Detroit, MI
J. J. Cantalupo, Ford Motor Company, Dearborn, MI
J. A. Colenso, Ford Motor Co., Dearborn, MI
E. A. Crilley, Ford Motor Co., Dearborn, MI
D. K. Haenchen, Volkswagen of America, Inc., Troy, MI
D. J. Helder, Donnelly Corporation, Holland, MI
H. Kopico, Plymouth, MI
H. H. Maruyama, Chrysler Corp., Detroit, MI
C. J. McLachlan, Ford Motor Co., Dearborn, MI
W. M. Miller, Navistar Int'l. Corp., Ft. Wayne, IN
R. L. Morrison, Ford Motor Co., Detroit, MI
J. C. Paschal, Ford Motor Co., Dearborn, MI
J. R. Repp, Grosse Ile, MI
R. A. Strasser, Ford Motor Company, Dearborn, MI

SAENORM.COM : Click to view the full PDF of j385_198604

MOTOR VEHICLE SEAT BELT ANCHORAGES--PERFORMANCE REQUIREMENTS

1. **SCOPE:** This SAE Recommended Practice specifies performance requirements for either static or dynamic testing of seat belt anchorages attached to vehicle structure or to the seat assemblies as installed in the motor vehicle. (This SAE Recommended Practice supersedes the Performance Requirements Section of SAE J787b.) Design Requirements and Test Procedures are specified in Recommended Practice SAE J383, Motor Vehicle Seat Belt Anchorages--Design Recommendations and Recommended Practice SAE J384, Motor Vehicle Seat Belt Anchorages--Test Procedure.

2. **DEFINITIONS:**

2.1 **Anchorage:** The final point of attachment for transferring seat belt assembly loads to the vehicle structure.

2.2 **Dynamic Test:** A test of anchorages through application of forces at onset rates which result from a barrier impact or equivalent sled simulation.

2.3 **Static Test:** A test in which loads are applied to the anchorage(s) at a rate less than the dynamic test through the use of hydraulic, pneumatic, etc. power.

2.4 **Seat Belt Assembly:** Any strap, webbing or similar device designed to secure a person in a motor vehicle with the intention of reducing the risk of bodily harm in an accident, including all buckles, adjusting mechanisms, fasteners, and related hardware. This SAE Recommended Practice covers anchorages for the following type of assemblies:

Type 1--Pelvic restraint belt (lap belt)

Type 2--Combination of Pelvic (lap) and upper torso (shoulder) restraint belts

Type 2a--Upper torso restraint (shoulder) belt for use only in conjunction with a lap belt as a Type 2 seat belt assembly.

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

3. GENERAL:

- 3.1 Simultaneous Testing: A simultaneous test of all anchorages shall be made separately for each full width seat or each set of laterally adjacent seats. A static load for dynamic load simulation shall be applied for each designated seating position for which the individual seat (front, rear, etc.) is designed using the original equipment seat belt assemblies or equivalent attachment hardware. The test shall be conducted in accordance with either the static or dynamic testing in paragraph 3 or 4 of SAE J384. Anchorages or attachment points may be tested separately, provided they are structurally remote from other anchorages.
- 3.2 Anchorages for Seat Belt Assemblies Attached to the Seat Structure: The seat assembly, seat adjusters, and attachments which are part of the occupant restraint system shall sustain the performance requirements statically as in paragraph 4 or dynamically as in paragraph 3 of SAE J384. However, when tested statically in accordance with paragraph 4 of SAE J384, the static equivalent of the seat inertia force in the forward direction (which is 20 x the weight of the seat systems as referenced in J879) will be applied to the cg of the seat simultaneously with the belt anchorage load.
- 3.3 Common Seat Belt Anchorages for Forward and Rearward Facing Seats: Common anchorages for forward and rearward facing seating positions need not be tested simultaneously.

4. STATIC TEST REQUIREMENTS:

4.1 Strength:

- 4.1.1 Anchorages for Type 1 Seat Belt (or Pelvic Portion of Type 2): When testing in accordance with paragraph 3 above, loadings for anchorages to the pelvic body block(s) shall be 5,000 lb (2268 kg) applied within 30 s and held for a duration of 10 s.
- 4.1.2 Anchorages for a Type 2 Seat Belt Assembly (or a Combination Type 1 and 2a): When testing in accordance with paragraph 3 above, loadings for an anchorage to the pelvic and upper torso body block(s) shall be 3000 lb (1361 kg) each applied within 30 s and held for a duration of at least 10 s.
- 4.2 Anchorages Mounted to Body Structure: Permanent deformation (or rupture) of any anchorage or the surrounding area shall not constitute failure providing it withstands the loads specified in Section 4.1 above.
- 4.3 Anchorages Attached to Seat Frames: Permanent deformation (or rupture) of any anchorage or the surrounding area including the seat structure shall not constitute failure providing it withstands the loads referenced in paragraph 3.2 above. There must be no failure or release of the seat adjuster mechanism or other locking device. The seat adjuster or locking device need not be operable after application of the test load.