



<b>SURFACE VEHICLE RECOMMENDED PRACTICE</b>	<b>J44</b>	<b>FEB2015</b>
	Issued	1973-10
	Reaffirmed	2015-02
Superseding J44 FEB2009		
Service Brake System Performance Requirements - Snowmobiles		

## RATIONALE

J44 has been reaffirmed to comply with the SAE five-year review policy.

### 1. SCOPE

This SAE Recommended Practice establishes performance requirements for hand-operated brake systems on recreational, noncompetition snowmobiles.

### 2. REFERENCES

#### 2.1 Applicable Publication

The following publication forms a part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue of SAE publication shall apply.

##### 2.1.1 SAE Publication

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), [www.sae.org](http://www.sae.org)

SAE J45 Brake System Test Procedure—Snowmobiles

#### 2.2 Related Publication

The following publication is provided for information purposes only and is not a required part of this specification.

##### 2.2.1 SAE Publication

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), [www.sae.org](http://www.sae.org)

SAE J1282 Snowmobile Brake Control Systems

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2015 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

**TO PLACE A DOCUMENT ORDER:** Tel: 877-606-7323 (inside USA and Canada)  
Tel: +1 724-776-4970 (outside USA)  
Fax: 724-776-0790  
Email: [CustomerService@sae.org](mailto:CustomerService@sae.org)  
<http://www.sae.org>

SAE WEB ADDRESS:

**SAE values your input. To provide feedback on this Technical Report, please visit**  
[http://www.sae.org/technical/standards/J44\\_201502](http://www.sae.org/technical/standards/J44_201502)

### 3. GENERAL REQUIREMENT

The brake systems shall be functional under winter operating conditions.

### 4. PERFORMANCE REQUIREMENTS

When subjected to the test procedures given in SAE J45, the following requirements must be satisfied by the service brake system:

#### 4.1 Preburnish Check

4.1.1 No component failure shall occur during the 400 N (90 lb) force application.

4.1.2 Deceleration shall be at least  $3 \text{ m/s}^2$  ( $10 \text{ ft/s}^2$ ).

#### 4.2 Burnish Procedure

No unusual variations in deceleration versus brake lever force shall occur during the burnishing operation.

#### 4.3 Effectiveness Test

4.3.1 Testing shall result in an average deceleration of at least  $6 \text{ m/s}^2$  ( $20 \text{ ft/s}^2$ ) or a locked track, if  $6 \text{ m/s}^2$  ( $20 \text{ ft/s}^2$ ) is unobtainable, from initial vehicle speeds of 32 and 64 km/h (20 and 40 mph).

4.3.2 During all phases of the test, no condition shall be permitted to cause the vehicle to lose stability due to track skid, to overturn, or to pull or swerve out of a test lane 1.2 m (4 ft) wider than the vehicle.

#### 4.4 Water Test

Deceleration shall be at least  $3 \text{ m/s}^2$  ( $10 \text{ ft/s}^2$ ).

#### 4.5 Fade and Recovery Test

##### 4.5.1 Fade Test

Each stop shall be achieved with a deceleration of at least  $4.6 \text{ m/s}^2$  ( $15 \text{ ft/s}^2$ ).

##### 4.5.2 Recovery Test

Testing shall result in an average deceleration of at least  $6 \text{ m/s}^2$  ( $20 \text{ ft/s}^2$ ) or a locked track, if  $6 \text{ m/s}^2$  ( $20 \text{ ft/s}^2$ ) is unobtainable, from an initial vehicle speed of 64 km/h (40 mph).

#### 4.6 Final Inspection

4.6.1 Unusual wear, scores, or cracks of the brake friction material which may interfere with braking function shall be reason for rejection.

4.6.2 All components of the brake system shall be intact and functional.