

A Product of the
Cooperative Engineering Program

SAE J598 MAY87

**Sealed Lighting Units
for Construction,
Industrial and Forest
Machinery**

SAE Recommended Practice
Revised May 1987

S. A. E.
LIBRARY

Submitted for Recognition as
an American National Standard

SAENORM.COM : Click to view the full PDF of SAE J598 MAY87

SAENORM.COM : Click to view the full PDF of j598_198705

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Copyright 1987 Society of Automotive Engineers, Inc.

SEALED LIGHTING UNITS FOR CONSTRUCTION,
INDUSTRIAL, AND FOREST MACHINERY

1. **SCOPE:** This recommended practice applies to floodlamp, headlamp and general service lamp units intended for use on off-road self-propelled work machines classified as construction (1.1 and 1.2), general purpose industrial (2) and forestry machines (4), as noted on SAE J1116. Construction and Industrial Machinery is normally operated off highways, therefore, this SAE Recommended Practice is not intended to be used as a basis for regulations by those having authority over motor vehicles used on public highways. Other performance and dimensional information is contained in SAE J572 and J760.
2. **DEFINITIONS:**
 - 2.1 Floodlamp (Trade No. 4078, 4478, 4578 - 145 mm (5-3/4 in) Nominal Diameter; 4406, 4410, 4593, 4752 - 114 mm (4-1/2 in) Nominal Diameter): Recommended for general illumination of area close to the machine.

Typical usage - Track type machine, front and rear lamps
Wheeled tractor scraper, front lamp
Scraper bowl illumination
Motorgrader illumination
Tractor shovel bucket illumination
Off-highway truck backup illumination
 - 2.2 General Service Lamp (Trapezoidal Beam), (Trade No. 4411, 4589 - 114 mm (4-1/2 in) Nominal Diameter): Recommended for general illumination.

Typical Usage - Wheeled tractor shovel, front lamp
Motorgrader, front lamp
 - 2.3 Headlamp (Trade No. 4080, 4480, 4880, 4813 - 145 mm (5-3/4 in) Nominal Diameter; 4750 - 114 mm (4-1/2 in) Nominal Diameter): The headlamp has a single beam with a sharp cutoff at the top to reduce glare to other vehicles and to minimize reflection from dust.

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

2.4 Headlamp (Trade No. 4814 - 145 mm (5-3/4 in) Nominal Diameter): This headlamp has a concentrated beam for high speed operation.

3. LABORATORY REQUIREMENTS:

3.1 The following sections of SAE J575 are a part of this recommended practice:

3.1.1 Section 2: Samples for Tests

3.1.2 Section 3: Laboratory Facilities

3.1.3 Section 4.6: Photometry. The photometric test shall be made with the photometer at a distance of at least 18.3 mm (60 ft) from the lamp. The unit shall be operated at its design voltage during the tests. For test values, see Tables 1-6. A tolerance of $\pm 1/4$ deg shall be allowed for any test point. Beam aim during photometric test shall be as follows:

1. Floodlamp and General Service Lamp Units: Visually center the beam vertically and horizontally on the photometer axis.

2. Headlamp Unit: Visually center the beam laterally on the photometer axis with the top cutoff of the beam 1 deg below photometer axis.

3. High-Speed Driving Lamp: Visually center the beam laterally on the photometer axis with the center of the high intensity zone $1/2$ deg down from the lamp center level.

3.2 Color Test: The color of the light from the lighting device shall be white, as defined in SAE J578.

4. PHYSICAL DIMENSIONS: Table 7 lists dimensional data for the lamps referred to in Tables 1 to 6.

5. ADDITIONAL SPECIFICATIONS: Table 7 lists electrical and life specifications.

6. ADDITIONAL INFORMATION: The units whose characteristics are shown in Tables 3 and 4 are also widely used for purposes other than construction and industrial machinery lighting. The tables are presented to facilitate lamp application and machine design.

7. INSTALLATION RECOMMENDATIONS: (These recommendations are not a part of the test specification.)

7.1 The units recommended have been evaluated for lighting performance with satisfactory results in average job situations when used as suggested under Definitions.

7.2 Dimensional interchangeability among types and voltages make it possible for the equipment designer or operator to choose units to suit the wide variety of lighting tasks met in service.

- 7.3 These units have been selected with special emphasis on light for working conditions and lamp durability which are best provided by units producing only a single beam. Because machines that travel on construction haul roads often encounter traffic similar to highway conditions, careful aiming of the lighting units is required. Headlamp systems composed of these single beam types have been made that restrict glare to acceptable limits, while maintaining adequate illumination for the work areas. This approach avoids the necessity of using dimming switches. Systems employing four or more units, combining headlamps and floodlamps, without dimming switches, have been devised which provide a marked improvement in operating efficiency.
- 7.4 Good results from a construction and industrial machinery lighting system require ample provision for individual adjustment of the lamp unit aim, depending on the particular lighting task. Some applications have been used to advantage with vertical aims from 30 deg below to 15 deg above the horizontal and with lateral aims from 15 deg left to 15 deg right.
- 7.5 Service life of units may be materially prolonged by mountings properly designed to cushion the unit from shock and vibration loading inherent in construction machinery. Where space permits, it is recommended that the 145 mm (5-3/4 in) nominal diameter units be specified to obtain maximum illumination.

TABLE 1 - TEST POINT VALUES FOR FLOODLAMP * 145 mm (5-3/4 IN) NOMINAL DIAMETER (Trade No. 4078, 4478, 4578)

Position, deg	Min cd	Position, deg	Min cd
10U-V	750	H-20R and 20L	500
10U-10R and 10L	500	5D-V	1,000
10U-20R and 20L	250	5D-10R and 10L	750
5U-V	1,000	5D-20R and 20L	500
5U-10R and 10L	750	10D-V	750
5U-20R and 20L	500	10D-10R and 10L	500
H-V	1,000	10D-20R and 20L	250
H-10R and 10L	750		

* The extremities of the beam should be diffused.

TABLE 2 - TEST POINT VALUES FOR HEADLAMP, 145 MM (5-3/4 IN) NOMINAL DIAMETER
(Trade No. 4080, 4480, 4880)

Position, deg	Max cd	Min cd	Position, deg	Max cd	Min cd
1U-10R and 10L	500	-	3D-10R and 10L	-	3,000
H-10R and 10L	1,000	-	3D-15R and 15L	-	1,500
1-1/2D-V	-	3,000	5D-V	-	3,000
1-1/2D-10R and 10L	-	1,500	5D-15R and 15L	-	750
1-1/2D-15R and 15L	-	1,000	8D-V	-	1,000
3D-V	-	6,000	8D-10R and 10L	-	600

TABLE 3 - TEST POINT VALUES FOR GENERAL SERVICE LAMP, 114 MM
(4-1/2 IN) NOMINAL DIAMETER (Trade No. 4411, 4589)

Position, deg	Min cd	Position, deg	Min cd
10U-V	1,500	H-8R and 8L	650
10U-5R and 5L	1,200	10D-V	500
H-V	1,000	10D-12R and 12L	300

TABLE 4 - TEST POINT VALUES FOR GENERAL SERVICE FLOODLAMP 114 MM
(4-1/2 IN) NOMINAL DIAMETER (Trade No. 4406, 4410, 4593)

Position, deg	Min cd	Position, deg	Min cd
15U-V	250	H-40R and 40L	175
15U-40R and 40L	125	15D-V	250
H-V	400	15D-40R and 40L	125

TABLE 5 - TEST POINT VALUES FOR HEADLAMP, 145 MM (5-3/4 IN) NOMINAL DIAMETER
(Trade No. 4813, 90W, Single Beam Headlamp Unit)

Position, deg	Max cd	Min cd	Position, deg	Max cd	Min cd
1U-10R and 10L	500	-	3D-10R and 10L	-	5,000
H-10R and 10L	1,000	-	3D-15R and 15L	-	2,000
1-1/2D-V	-	5,000	5D-V	-	5,000
1-1/2D-10R and 10L	-	2,000	5D-15R and 15L	-	450
1-1/2D-15R and 15L	-	500	8D-V	-	500
3D-V	-	10,000	8D-10R and 10L	-	300

TABLE 6 - TEST POINT VALUES FOR HEADLAMP, 145 MM (5-3/4 IN) NOMINAL DIAMETER
(Trade No. 4814, 90W, High-Speed Driving Lamp Unit)

Position, deg	Max cd	Min cd	Position, deg	Max cd	Min cd
1U-10R and 10L	600	-	3D-10R and 10L	-	400
H-10R and 10L	1,500	-	3D-15R and 15L	-	100
1-1/2D-V	-	20,000	5D-V	-	3,500
1-1/2D-10R and 10L	-	700	5D-15R and 15L	-	100
1-1/2D-15R and 15L	-	100	8D-V	-	500
3D-V	-	12,000	8D-10R and 10L	-	100

SAENORM.COM : Click to view the full PDF of J598-198705

TABLE 7 - SEALED UNITS FOR CONSTRUCTION AND INDUSTRIAL MACHINES

TYPE OF SERVICE (a)	TRADE NO.	DESIGN		RATED AVERAGE LAB LIFE Hr at V.	MAX AMP OF DESIGN VOLTS	FILAMENT TYPE	BULB SIZE	MAXIMUM DIAMETER		MAX OVERALL LENGTH		DIMENSIONAL SPECIFICATION	TERMINAL
		WATTS	VOLTS					mm	in	mm	in		
6 VOLT CIRCUITS													
1	4078	50	6.4	500 at 7	8.2	C-6	PAR 46	144.78	5.70	101.6	4	Fig. 1 (b)	Lug
2	4080	50	6.4	500 at 7	8.2	C-6	PAR 46	144.78	5.70	101.6	4	Fig. 1 (b)	Lug
12 VOLT CIRCUITS													
1	4406	35	12.8	300 at 14	2.93	C-6	PAR 36	113.28	4.46	69.85	2-3/4	Fig. 2 (c)	Screw
1	4410	35	12.8	300 at 14	2.93	C-6	PAR 36	113.28	4.46	69.85	2-3/4	Fig. 2 (c)	Screw
3	4411	35	12.8	300 at 14	2.93	C-6	PAR 36	113.28	4.46	69.85	2-3/4	Fig. 2 (c)	Screw
1	4478	60	13	800 at 14	4.9	2-C6 in Ser.	PAR 46	144.78	5.70	101.6	4	Fig. 1 (b)	Lug
2	4480	60	13	800 at 14	4.9	2-C6 in Ser.	PAR 46	144.78	5.70	101.6	4	Fig. 1 (b)	Lug
24 VOLT CIRCUITS													
1	4578	60	28	800 at 28	2.3	2-C6 in Ser.	PAR 46	144.78	5.70	101.6	4	Fig. 1 (b)	Lug
3	4589	50	28	400 at 28	1.95	CC-6	PAR 36	113.28	4.46	69.85	2-3/4	Fig. 2 (c)	Screw
1	4593	50	28	400 at 28	1.95	CC-6	PAR 36	113.28	4.46	69.85	2-3/4	Fig. 2 (c)	Screw
2	4750	60	28	800 at 28	2.3	2-C6 in Ser.	PAR 36	113.28	4.46	69.85	2-3/4	Fig. 2 (c)	Screw
1	4752	60	28	800 at 28	2.3	2-C6 in Ser.	PAR 36	113.28	4.46	69.85	2-3/4	Fig. 2 (c)	Screw
2	4813	90	28	800 at 28	3.4	2-C6 in Ser.	PAR 46	144.78	5.70	101.6	4	Fig. 1 (b)	Lug
4	4814	90	28	800 at 28	3.4	2-C6 in Ser.	PAR 46	144.78	5.70	101.6	4	Fig. 1 (b)	Lug
2	4880	60	28	800 at 28	2.3	2-C6 in Ser.	PAR 46	144.78	5.70	101.6	4	Fig. 1 (b)	Lug

NOTE: Service life of construction machine light units might not equal laboratory life because of vibration, shock and variations in vehicle voltage.

(a) Numbers designate type of service

- 1 - Floodlamp
- 2 - Headlamp
- 3 - General Service Lamp
- 4 - High-speed Driving Lamp

(b) See SAE J572

(c) See SAE J760