

**ENGINE MOUNTINGS**

**Foreword**—This Reaffirmed Document has been changed only to reflect the new SAE Technical Standards Board Format.

1. **Scope**—This SAE Standard defines engine mounting dimensions for industry standardization and interchangeability. Table 1 and Figure 1 are dimensions for arm type mountings. Table 2 and Figure 2 are for side pad mountings. For engine housing SAE flange dimensions, see SAE J617. For engine foot type mountings (front and rear), see SAE J616.

2. **References**

2.1 **Applicable Publications**—The following publications form a part of this document to the extent specified herein. Unless otherwise specified, the latest issue of SAE publications shall apply.

2.1.1 SAE PUBLICATIONS—Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

SAE J616—Engine Foot Mounting (Front and Rear)

SAE J617—Engine Flywheel Housings

**TABLE 1A—ARM TYPE MOUNTING DIMENSIONS—REFER TO FIGURES 1 AND 2**

SAE Arm No. Tolerance	A mm ±0.25	A in ±0.010	B mm ±0.25	B in ±0.010	C mm ±3.18	C in ±0.12	D mm ±0.25	D in ±0.010
1	298.45	11.750	339.73	13.375	365.13	14.375	50.80	2.000
3	285.75	11.250	311.15	12.250	327.03	12.875	63.50	2.500
4	285.75	11.250	311.15	12.250	327.03	12.875	63.50	2.500
5	285.75	11.250	311.15	12.250	327.03	12.875	63.50	2.500
2T	254.0	10.000	276.23	10.875	298.45	11.750	76.20	3.000

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

QUESTIONS REGARDING THIS DOCUMENT: (724) 772-8512 FAX: (724) 776-0243  
TO PLACE A DOCUMENT ORDER; (724) 776-4970 FAX: (724) 776-0790  
SAE WEB ADDRESS <http://www.sae.org>

TABLE 1B—ARM TYPE MOUNTING DIMENSIONS—REFER TO FIGURES 1 AND 2

SAE Arm No. Tolerance	E mm ±0.25	E in ±0.010	F mm ±0.25	F in ±0.010	R mm Max	R in Max	M mm ±0.25	M in ±6.35
1	76.20	3.000	19.84	0.781	11.2	0.44	4.00	101.6
3	76.20	3.000	16.66	0.656	6.4	0.25	3.50	88.9
4	76.20	3.000	16.66	0.656	6.4	0.25	2.75	69.8
5	76.20	3.000	16.66	0.656	6.4	0.25	2.75	69.8
2T	76.20	3.000	16.66	0.656	6.4	0.25	4.00	101.6




FIGURE 1—ARM TYPE MOUNTING DIMENSIONS

**SAE J615 Reaffirmed JUL95**

**TABLE 2A—SIDE PAD MOUNTING DIMENSIONS FLAT OR LOCATING LEDGE TYPE—REFER TO FIGURE 2**

SAE PAD No. <sup>(1)</sup> Tolerance	A mm ±0.25	A in ±0.010	B mm ±0.25	B in ±0.010	C mm ±0.25	C in ±0.010	D mm ±0.25	D in ±0.010
00	—	—	—	—	—	—	—	—
0	88.90	3.500	114.30	4.500	19.05	0.750	25.40	1.000
1/2	88.90	3.500	114.30	4.500	19.05	0.750	25.40	1.000
1	63.50	2.500	88.90	3.500	15.88	0.625	44.45	1.750
2	63.50	2.500	88.90	3.500	15.88	0.625	44.45	1.750
3	50.80	2.000	66.68	2.625	15.88	0.625	42.88	1.688
4	50.80	2.000	66.68	2.625	15.88	0.625	42.88	1.688
5	50.80	2.000	66.68	2.625	15.88	0.625	42.88	1.688
6	50.80	2.000	66.68	2.625	15.88	0.625	42.88	1.688

**TABLE 2B—SIDE PAD MOUNTING DIMENSIONS FLAT OR LOCATING LEDGE TYPE—REFER TO FIGURE 2**

SAE Pad No. <sup>(1)</sup> Tolerance	E mm ±0.25	E in ±0.010	Tapped Hole Size <sup>(2)</sup>	F mm ±0.25	F in ±0.010	G mm ±3.18	G in ±0.12	R mm Max	R in Max
00	—	—	—	—	—	—	—	—	—
0	368.30	14.500	5/8–11	19.05	0.750	381.30	15.01	1.3	0.05
1/2	330.20	13.000	5/8–11	19.05	0.750	343.20	13.51	1.3	0.05
1	285.75	11.250	5/8–11	19.05	0.750	298.75	11.76	1.3	0.05
2	260.35	10.250	1/2–13	15.87	0.625	269.85	10.63	1.3	0.05
3	260.35	10.250	1/2–13	15.87	0.625	269.85	10.63	0.8	0.03
4	212.72	8.375	1/2–13	15.87	0.625	222.22	8.88	0.8	0.03
5	212.72	8.375	1/2–13	15.87	0.625	222.22	8.88	0.8	0.03
6	187.32	7.375	1/2–13	15.87	0.625	196.82	7.78	0.8	0.03

1. Pads of a given number can be matched with housings of the same SAE number or smaller size (larger SAE number).
2. Tapped holes shall be threaded in accordance with UNC Class 2B tolerances of ANSI B1.1, threads. The minimum length of thread engagement shall be 1.5 times the nominal diameter for gray iron housings and 2 times the nominal diameter for aluminum housings.




FIGURE 2—SIDE PAD MOUNTING DIMENSIONS

PREPARED BY THE SAE CLUTCH, FLYWHEEL, AND HOUSING STANDARDS COMMITTEE