

Issued	1954-10
Reaffirmed	2002-08

Superseding J682 OCT1984

Rear Wheel Splash and Stone Throw Protection

Foreword—This Document has not changed other than to put it into the new SAE Technical Standards Board Format. The Scope is Section 1 and References were added as Section 2.

1. **Scope**—For guidance only in regard to highway commercial motor vehicles where protection to the rear against rear wheel splash and stone throw is deemed necessary, the following clearance specifications are recommended.
2. **References**—There are no referenced publications specified herein.
3. **Splash and Stone Throw Clearance**—The vertical measure from the ground to the bottom edge of the wheel house, fender, guard, or other splash and throw limiting part of the vehicle, shall not exceed one-third of the horizontal distance from that bottom edge to the center line of the axle. However, such limiting part need be no closer to the road than 15.24 cm (6 in), when the vehicle is loaded.¹
4. The splash and throw limiting part shall extend laterally for at least the width of the tire or tires.
5. The splash and throw limiting part shall be as far to the rear from the wheel as practical, for greatest efficiency. See Figure 1.

1. To clear curb, snow, mud, ice, or other road obstructions.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.


Copyright ©2002 Society of Automotive Engineers, Inc.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER:

Tel: 877-606-7323 (inside USA and Canada)
 Tel: 724-776-4970 (outside USA)
 Fax: 724-776-0790
 Email: custsvc@sae.org
<http://www.sae.org>

SAE WEB ADDRESS:



VERTICAL HEIGHT (H) TO BE NOT MORE THAN
1/3 OF HORIZONTAL DISTANCE (D)

FIGURE 1—SPLASH AND STONE THROW CLEARANCE

PREPARED BY THE SAE TRUCK AND BUS CHASSIS COMMITTEE

SAENORM.COM : Click to view the full PDF of j682_200208