

Submitted for recognition as an American National Standard

TIRE SELECTION TABLES FOR AGRICULTURAL TRACTORS OF FUTURE DESIGN

Foreword—This Document has also changed to comply with the new SAE Technical Standards Board format.

1. **Scope**—This SAE Recommended Practice is established for the purpose of providing selection tables of tires preferred for application to machines of future design.

The objective of Tables 1 and 2 is to minimize the number of tire sizes.

TABLE 1—PREFERRED DRIVE TIRE SIZES FOR USE ON AGRICULTURAL MACHINES OF FUTURE DESIGN

Grouped by Rim Dia, in	Tire Size	Ply Rating	Std Rim Width, in	Design Section Width, in	Static Loaded Radius, in	Design Overall Dia, in
Code R-1 (Regular Agricultural)						
16	9.5 — 16	4	W8, W8L, 8LB	9.5	15.1	33.26
	18.4 — 16.1	6	16.1 — 16LB	18.4	19.5	44.76
24	8.3 — 24	4	W — 7	8.3	18.1	39.10
	9.5 — 24	4	W — 8	9.5	19.0	41.26
	11.2 — 24	4	W — 10	11.2	19.8	43.44
	12.4 — 24	4, 6, 8	W — 11	12.4	20.8	45.62
	13.6 — 24	4	W — 12	13.6	21.5	47.62
	14.9 — 24	6	W — 13	14.9	22.4	49.82
26	16.9 — 24	6, 8	W — 15L	16.9	23.4	52.48
	14.9 — 26	6, 8	W — 13	14.9	23.5	51.82
	16.9 — 26	6, 8	W — 15L	16.9	24.4	54.48
	18.4 — 26	6, 8, 10	W — 16L, DW — 16	18.4	25.5	57.10
	23.1 — 26	8, 10	DW — 20	23.1	28.0	63.20
28	28L — 26	10	DW — 25	28.1	28.2	63.60
	11.2 — 28	4	W — 10	11.2	21.8	47.44
	12.4 — 28	4	W — 11	12.4	22.6	49.62
	13.6 — 28	4, 6	W — 12	13.6	23.5	51.62
	14.9 — 28	6	W — 13	14.9	24.4	53.82
16.9 — 28	6, 8	W — 15L	16.9	25.4	56.48	

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

QUESTIONS REGARDING THIS DOCUMENT: (724) 772-8512 FAX: (724) 776-0243
TO PLACE A DOCUMENT ORDER; (724) 776-4970 FAX: (724) 776-0790
SAE WEB ADDRESS <http://www.sae.org>

SAE J711 Revised MAR91

TABLE 1—PREFERRED DRIVE TIRE SIZES FOR USE ON AGRICULTURAL MACHINES OF FUTURE DESIGN (CONTINUED)

Grouped by Rim Dia, in	Tire Size	Ply Rating	Std Rim Width, in	Design Section Width, in	Static Loaded Radius, in	Design Overall Dia, in
	18.4 — 28	6	W — 16L, DW — 16	18.4		26.6 59.10
30	14.9 — 30	6	W — 13	14.9		25.5 55.82
	16.9 — 30	6	W — 15L	16.9		26.5 58.48
	18.4 — 30	6, 8, 10	W — 16L, DW — 16	18.4		27.4 61.10
	23.1 — 30	8	DW — 20	23.1		29.8 67.20
32	24.5 — 32	10	DW — 21	24.5		31.5 71.00
34	16.9 — 34	6	W — 15L	16.9		28.5 62.48
	18.4 — 34	6, 8, 10	W — 16L, DW — 16	18.4		29.5 65.10
	20.8 — 34	8	W — 18L	20.8		30.3 68.20
	23.1 — 34	8	DW — 20	23.1		31.8 71.20
36	13.9 — 36	6	W — 12, DW — 12	13.9		26.8 58.20
38	13.6 — 38	4, 6	W — 12, DW — 12	13.6		28.5 61.62
	15.5 — 38	6, 8	W — 14L, DW — 14	15.5		28.5 61.76
	16.9 — 38	6, 8	W — 15L	16.9		30.4 66.48
	18.4 — 38	6, 8, 10, 12	W — 16L	18.4		31.5 69.10
	20.8 — 38	8, 10	W — 18L	20.8		32.6 72.20
CODE R-2 (Cane and Rice)						
26	18.4 — 26	6, 8, 10	W — 16L, DW — 16	18.4		26.2 58.96
	23.1 — 26	8, 10	DW — 20	23.1		29.3 65.44
	28L — 26	10	DW — 25	28.1		29.4 65.86
30	23.1 — 30	8	DW — 20	23.1		31.2 69.44
32	24.5 — 32	10	DW — 21	24.5	32.8	73.34
34	18.4 — 34	6, 8	W — 16L, DW — 16	18.4	30.1	66.96
	20.8 — 34	8	W — 18L	20.8	31.4	70.25
	23.1 — 34	8	DW — 20	23.1	33.1	73.44
38	15.5 — 38	6	W — 14L	15.5	30.0	63.18
	18.4 — 38	6, 8, 10	W — 16L	18.4	32.0	70.96
	20.8 — 38	8, 10	W — 18L	20.8	33.4	74.26
CODE R-3 (Industrial and Sand)						
16	9.5 — 16	4	W — 8, W8L, 8LB	9.5	14.7	32.30
	12.4 — 16	6, 8	W — 11	12.4	16.3	36.66
	18.4 — 16.1	6, 8	16.1 — 16LB	18.4	18.9	43.80
24	8.3 — 24	4	W — 7	8.3	17.8	38.14
	9.5 — 24	4	W — 8	9.5	18.4	40.30

SAE J711 Revised MAR91

TABLE 1—PREFERRED DRIVE TIRE SIZES FOR USE ON AGRICULTURAL MACHINES OF FUTURE DESIGN (CONTINUED)

Grouped by Rim Dia, in	Tire Size	Ply Rating	Std Rim Width, in	Design Section Width, in	Static Loaded Radius, in	Design Overall Dia, in
26	14.9 — 24	6	W — 13	14.9	22.4	48.86
	16.9 — 24	6	W — 15L	16.9	22.8	51.52
	16.9 — 26	6	W — 15L	16.9	23.8	53.52
	18.4 — 26	6, 10	W — 16L, DW — 16	18.4	25.3	56.14
	23.1 — 26	8	DW — 20	23.1	26.9	62.24
CODE R-4 (Industrial Tractor, Intermediate Tread)						
24	14.9 — 24	6, 8	W — 13	14.9	22.2	48.86
	16.9 — 24	6, 8, 10	W — 15L	16.9	23.1	51.52
	17.5L — 24	6	W — 15L	17.5	22.0	48.84
28	14.9 — 28	6, 8	W — 13	14.9	24.2	52.86
	16.9 — 28	6, 8	W — 15L	16.9	25.1	55.52

SAENORM.COM : Click to view the full PDF of J711 - 139103

SAE J711 Revised MAR91

TABLE 2—PREFERRED STEERING TIRE SIZES FOR USE ON AGRICULTURAL MACHINES OF FUTURE DESIGN

Grouped by Rim Dia, in	Tire Size	Ply Rating	Std Rim Width, in	Design Section Width, in	Static Loaded Radius, in	Design Overall Dia, in
CODE F-1 (Single Rib)						
16	10.00 — 16SL	6	W8L, W8, 8LB	10.8	16.3	35.66
	11.00 — 16SL	8	W10L, 10LB	12.4	17.8	38.54
18	7.50 — 18SL	6	5.50F	8.0	16.1	34.26
20	7.50 — 20SL	6	5.50F	8.0	17.2	36.26
CODE F-2 (Regular Agricultural)						
12	4.00 — 12SL	4	3.00D	4.4	10.0	21.24
14	6.00 — 14SL	4	5KB	6.6	12.6	27.10
15	5.00 — 15SL	4	3.00D	5.1	12.0	26.14
	7.5L — 15SL	6, 8	6LB	8.2	13.5	29.36
	9.5L — 15SL	6, 8	W8L, 8LB	9.5	13.9	30.80
	11L — 15SL	6, 8	W8L, 8LB	11.0	14.4	32.00
16	5.50 — 16SL	4	4.00E	5.9	13.2	28.06
	6.00 — 16SL	4, 6	4.00E	6.2	13.5	29.10
	6.50 — 16SL	4, 6	4.50E	6.8	13.9	29.96
	7.50 — 16SL	4, 6, 8	5.50F	8.0	14.8	31.80
	10.00 — 16SL	6, 8	W81, W8, 8LB	10.8	16.0	35.20
	11.00 — 16SL	6, 8	W10L, 10LB	12.4	17.3	38.08
	14L — 16.1SL	6	W11C — 16.1	14.0	17.4	38.80
18	7.50 — 18SL	4, 6	5.50F	8.0	15.9	33.80
20	7.50 — 20SL	6	5.50F	8.0	17.0	35.80
	9.50 — 20SL	6, 8	W7L	10.0	17.8	38.50
CODE F-3 (Industrial Multiple Rib)						
10	9.00 — 10SL	4	6.00F	9.2	12.2	26.54
16	7.50 — 16SL	6	5.50F	8.0	14.7	30.78
	11.00 — 16SL	6, 8	W10L, 10LB	12.4	16.8	36.80

NOTES: For vehicle design clearance purposes:

1. Maximum grown tire widths may exceed the above design new tire section widths by 8% for drive tires and 9% for steering wheel tires.
2. Maximum grown tire outside diameters may exceed the above design new tire outside diameters for drive tires by 6% and for steering wheel tires by 8% of the difference between the design new tire outside diameter and the nominal rim diameter.