

S. A. E.  
LIBRARY

**Tire Selection Tables for  
Agricultural and Light  
Industrial Machines of Future  
Design — SAE J711c**

**SAE RECOMMENDED PRACTICE  
LAST REVISED MAY 1975**

SAENORM.COM : Click to view the full PDF of J711c\_197505



TIRE SELECTION TABLES FOR  
 AGRICULTURAL AND LIGHT INDUSTRIAL  
 MACHINES OF FUTURE DESIGN -  
 SAE J711c

SAE Recommended Practice

Report of Tractor Technical Committee approved  
 June 1960 and last revised May 1975.

This SAE Recommended Practice is established for the purpose of providing selection tables of tires preferred for application

to machines of future design. The objective of the table is to minimize the number of tire sizes.

TABLE 1 - PREFERRED DRIVE TIRE SIZES FOR USE ON AGRICULTURAL MACHINES OF FUTURE DESIGN

Grouped by Rim Dia In	Tire Size	Ply Rating	Std Rim Width In	Design Section Width In	Static Loaded Radius, In	Design Overall Dia In
Code R-1 (Regular Agricultural)						
16	9.5-16 18.4-16.1	4 6	W-8, W8L, 8LB 16.1-16LB	9.5 18.4	15.1 19.5	33.26 44.76
24	8.3-24 9.5-24 11.2-24 12.4-24 13.6-24 14.9-24 16.9-24	4 4 4 4,6,8 4 6 6,8	W-7 W-8 W-10 W-11 W-12 W-13 W-15L	8.3 9.5 12.2 12.4 13.6 14.9 16.9	18.1 19.0 19.8 20.8 21.5 22.4 23.4	39.10 41.26 43.44 45.62 47.52 49.82 52.48
26	14.9-26 16.9-26 18.4-26 23.1-26 28L-26	6,8 6,8 6,8,10 8,10 10	W-13 W-15L W-16L, DW-16 DW-20 DW-25	14.9 16.9 18.4 23.1 28.1	23.5 24.4 25.5 28.0 28.2	51.82 54.48 57.10 63.20 63.60
28	11.2-28 12.4-28 13.6-28 14.9-28 16.9-28 18.4-28	4 4 4,6 6 6,8 6	W-10 W-11 W-12 W-13 W-15L W-16L, DW-16	11.2 12.4 13.6 14.9 16.9 18.4	21.8 22.6 23.5 24.4 25.4 26.6	47.44 49.62 51.62 53.82 56.48 59.10
30	14.9-30 16.9-30 18.4-30 23.1-30	6 6 6,8,10 8	W-13 W-15L W-16L, DW-16 DW-20	14.9 16.9 18.4 23.1	25.5 26.5 27.4 29.8	55.82 58.48 61.10 67.20
32	24.5-32	10	DW-21	24.5	31.5	71.00
34	16.9-34 18.4-34 20.8-34 23.1-34	6 6,8,10 8 8	W-15L W-16L, DW-16 W-18L DW-20	16.9 18.4 20.8 23.1	28.5 29.5 30.3 31.8	62.48 65.10 68.20 71.20
36	13.9-36	6	W-12, DW-12	13.9	26.8	58.20
38	13.6-38 15.5-38 16.9-38 18.4-38 20.8-38	4,6 6,8 6,8 6,8,10,12 8,10	W-12, DW-12 W-14L, DW-14 W-15L W-16L W-18L	13.6 15.5 16.9 18.4 20.8	28.5 28.5 30.4 31.5 32.6	61.62 61.76 66.48 69.10 72.20
Code R-2 (Cane and Rice)						
26	18.4-26 23.1-26 28L-26	6,8,10 8,10 10	W-16L, DW-16 DW-20 DW-25	18.4 23.1 28.1	26.2 29.3 29.4	58.96 65.44 65.86
30	23.1-30	8	DW-20	23.1	31.2	69.44
32	24.5-32	10	DW-21	24.5	32.8	73.34
34	18.4-34 20.8-34 23.1-34	6,8 8 8	W-16L, DW-16 W-18L DW-20	18.4 20.8 23.1	30.1 31.4 33.1	66.96 70.25 73.44
38	15.5-38 18.4-38 20.8-38	6 6,8,10 8,10	W-14L W-16L W-18L	15.5 18.4 20.8	30.0 32.0 33.4	63.18 70.96 74.26
Code R-3 (Industrial and Sand)						
16	9.5-16 12.4-16 18.4-16.1	4 6,8 6,8	W-8, W8L, 8LB W-11 16.1-16LB	9.5 12.4 18.4	14.7 16.3 18.9	32.30 36.66 43.80
24	8.3-24 9.5-24 14.9-24 16.9-24	4 4 6 6	W-7 W-8 W-13 W-15L	8.3 9.5 14.9 16.9	17.8 18.4 22.4 22.8	38.14 40.30 48.86 51.52
26	16.9-26 18.4-26 23.1-26	6 6,10 8	W-15L W-16L, DW16 DW-20	16.9 18.4 23.1	23.8 25.3 26.9	53.52 56.14 62.24
Code R-4 (Industrial Tractor, Intermediate Tread)						
24	14.9-24 16.9-24 17.5L-24	6,8 6,8,10 6	W-13 W-15L W-15L	14.9 16.9 17.5	22.2 23.1 22.0	48.86 51.52 48.84
28	14.9-28 16.9-28	6,8 6,8	W-13 W-15L	14.9 16.9	24.2 25.1	52.86 55.52

**TABLE 2 - PREFERRED STEERING TIRE SIZES FOR USE ON AGRICULTURAL MACHINES OF FUTURE DESIGN**

Grouped by Rim Dia In	Tire Size	Ply Rating	Std Rim Width In	Design Section Width In	Static Loaded Radius In	Design Overall Dia In
Code F-1	(Single Rib)					
16	10.00-16 SL	6	W8L, W8, 8LB	10.8	16.3	35.66
	11.00-16 SL	8	W10L, 10LB	12.4	17.8	38.54
18	7.50-18 SL	6	5.50F	8.0	16.1	34.26
20	7.50-20 SL	6	5.50F	8.0	17.2	36.26
Code F-2	(Regular Agricultural)					
12	4.00-12 SL	4	3.00D	4.4	10.0	21.24
14	6.00-14 SL	4	5KB	6.6	12.6	27.10
15	5.00-15 SL	4	3.00D	5.1	12.0	26.14
	7.5L-15 SL	6,8	6LB	8.2	13.5	29.36
	9.5L-15 SL	6,8	W8L, 8LB	9.5	13.9	30.08
	11L-15 SL	6,8	W8L, 8LB	11.0	14.4	32.00
16	5.50-16 SL	4	4.00E	5.9	13.2	28.06
	6.00-16 SL	4,6	4.00E	6.2	13.5	29.10
	6.50-16 SL	4,6	4.50E	6.8	13.9	29.96
	7.50-16 SL	4,6,8	5.50F	8.0	14.8	31.80
	10.00-16 SL	6,8	W8L, W8, 8LB	10.8	16.0	35.20
	11.00-16 SL	6,8	W10L, 10LB	12.4	17.3	38.08
	14L-16.1 SL	6	W11C-16.1	14.0	17.4	38.80
18	7.50-18 SL	4,6	5.50F	8.0	15.9	33.80
20	7.50-20 SL	6	5.50F	8.0	17.0	35.80
	9.50-20 SL	6,8	W7L	10.0	17.8	38.50
Code F-3	(Industrial Multiple Rib)					
10	9.00-10 SL	4	6.00F	9.2	12.2	26.54
16	7.50-16 SL	6	5.50F	8.0	14.7	30.78
	11.00-16 SL	6,8	W10L, 10LB	12.4	16.8	36.80
Code I-1	(Rib Implement)					
9	4.00-9SL	4	3.00D	4.4	8.1	17.44
10	9.00-10 SL	4	6.00F	9.2	11.1	26.60
12	4.00-12 SL	4	3.00D	4.4	9.5	20.44
	8.5L-14 SL	6,8	6KB	8.5	12.8	28.38
14	9.5L-14 SL	6,8	8KB	9.5	13.1	29.18
	11L-14 SL	6	8KB	11.0	13.2	29.60
15	5.00-15 SL	4	3.00D	5.1	11.4	25.16
	5.90-15 SL	4	4-1/2KB	5.9	12.0	26.20
	6.40-15 SL	4,6	4-1/2KB	6.4	12.4	26.92
	6.70-15 SL	4,6	4-1/2KB	6.7	12.7	27.70
	7.60-15 SL	4,6,8	5-1/2KB	7.6	13.1	28.90
	9.5L-15 SL	8	W8L, 8LB	9.5	13.4	30.18
	10.00-15 SL	8	8LB, W8L	10.8	14.8	33.60
	11L-15 SL	6,8,10	8LB, W8L	11.0	13.8	30.60
	12.5L-15 SL	6,8	10LB	12.5	14.3	32.40
	16	5.50-16 SL	4	4.00E	5.9	12.3
6.00-16 SL		4,6	4.00E	6.2	12.6	28.04
6.50-16 SL		4,6,8	4.50E	6.8	13.0	28.92
7.50-16 SL		4,6,8,10	5.50F	8.0	14.0	30.92
9.00-16 SL		8,10	6.00F	9.2	15.0	33.40
11L-16 SL		6,8,10	W8, W8L, 8LB	11.0	14.3	31.60
12.5L-16SL		8	W10L, 10LB	12.5	14.8	33.40
18		4.00-18 SL	2,4	3.00D	4.4	12.5
	7.50-18 SL	4,6	5.50F	8.0	15.0	32.92
20	7.50-20 SL	4,6	5.50F	8.0	16.0	34.92
24	7.50-24 SL	4	W7	8.8	18.0	39.26
	9.00-24 SL	6,8	W8	10.7	19.4	43.06
	11.25-24 SL	8	W10H	12.8	21.0	46.10
28	11.25-28 SL	10	W10H	12.8	23.0	50.10
Code I-2	(Moderate Traction)					
16	13.50-16.1 SL	6,8	W11C-16.1	13.9	17.4	40.70
	16.5L-16.1 SL	6,8,10	16.1-14LB	16.5	17.3	40.80
Code I-3	(Traction Implement)					
15	5.00-15 SL	4	3.00D	5.1	11.6	25.78
	5.90-15 SL	4	4-1/2KB	5.9	12.2	26.82
	6.70-15 SL	4	4-1/2KB	6.7	12.8	28.35
	12.5L-15 SL	6,8	10 LB	12.5	14.4	33.15
16	7.50-16 SL	4	5.50F	8.0	14.1	31.54
	13.50-16.1 SL	6	W11C-16.1	13.9	17.5	41.08
18	7.50-18 SL	4	5.50F	8.0	15.2	33.54
20	7.50-20 SL	4	5.50F	8.0	16.2	35.54
24	7.50-24 SL	4	W7	8.8	18.3	39.88
Code I-6	(Smooth Implement)					
8	4.00-8 SL	2,4	3.00D	4.4	7.4	16.00

SAENORM.COM · Click to view the full PDF of J771C-197505