



UL 141

STANDARD FOR SAFETY

Garment Finishing Appliances

[ULNORM.COM](https://www.ulnorm.com) : Click to view the full PDF of UL 141 2025

[ULNORM.COM](https://ulnorm.com) : Click to view the full PDF of UL 141 2025

UL Standard for Safety for Garment Finishing Appliances, UL 141

Ninth Edition, Dated March 30, 2011

Summary of Topics

This reaffirmation of ANSI/UL 141 dated January 23, 2025 is being issued to update the title page to reflect the most recent designation as a Reaffirmed American National Standard (ANS). No technical changes have been made.

Text that has been changed in any manner or impacted by ULSE's electronic publishing system is marked with a vertical line in the margin.

The requirements are substantially in accordance with Proposal(s) on this subject dated December 6, 2024.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of ULSE Inc. (ULSE).

ULSE provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will ULSE be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if ULSE or an authorized ULSE representative has been advised of the possibility of such damage. In no event shall ULSE's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold ULSE harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 141 2025

MARCH 30, 2011
(Title Page Reprinted: January 23, 2025)



ANSI/UL 141-2020 (R2025)

1

UL 141

Standard for Garment Finishing Appliances

First Edition – June, 1936
Second Edition – June, 1940
Third Edition – April, 1954
Fourth Edition – May, 1973
Fifth Edition – April, 1985
Sixth Edition – November, 1991
Seventh Edition – February, 1996
Eighth Edition – June, 2007

Ninth Edition

March 30, 2011

This ANSI/UL Standard for Safety consists of the Ninth Edition including revisions through January 23, 2025.

The most recent designation of ANSI/UL 141 as a Reaffirmed American National Standard (ANS) occurred on January 23, 2025. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, and Title Page.

Comments or proposals for revisions on any part of the Standard may be submitted to ULSE at any time. Proposals should be submitted via a Proposal Request in the Collaborative Standards Development System (CSDS) at <https://csds.ul.com>.

Our Standards for Safety are copyrighted by ULSE Inc. Neither a printed nor electronic copy of a Standard should be altered in any way. All of our Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of ULSE Inc.

© 2025 ULSE Inc. All rights reserved.

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 141 2025

CONTENTS

INTRODUCTION

1 Scope7
 2 Glossary7
 3 General8
 3.1 Units of measurement8
 3.2 Undated references8

CONSTRUCTION

4 General8
 5 Components8
 5.1 General8
 5.2 Attachment plugs, receptacles, connectors, and terminals10
 5.3 Batteries and battery chargers11
 5.4 Boxes and raceways11
 5.5 Capacitors and filters11
 5.6 Controls12
 5.7 Cords, cables, and internal wiring14
 5.8 Cord reels14
 5.9 Film-coated wire (magnet wire)15
 5.10 Gaskets and seals15
 5.11 Ground-fault, arc-fault, and leakage current detectors/interrupters15
 5.12 Heaters, heating elements and pads15
 5.13 Insulation systems16
 5.14 Light sources and associated components16
 5.15 Marking and labeling systems16
 5.16 Motors and motor overload protection17
 5.17 Overcurrent protection19
 5.18 Polymeric materials and enclosures20
 5.19 Power supplies20
 5.20 Printed wiring boards20
 5.21 Semiconductors and small electronic components20
 5.22 Supplemental insulation, insulating bushings, and assembly aids21
 5.23 Switches22
 5.24 Transformers22
 5.25 Valves (electrically operated) and solenoids23
 5.26 Video and audio components23
 6 Enclosure23
 6.1 General23
 6.2 Polymeric material enclosure27
 7 Handles28
 8 Provision for Mounting29
 9 Mechanical Assembly29
 10 Protection Against Corrosion29
 11 Accessibility of Uninsulated Live Parts30
 12 Supply Connections33
 12.1 Permanently connected appliance33
 12.2 Cord-connected appliances35
 13 Grounding40
 14 Current-Carrying Parts40
 15 Internal Wiring41
 15.1 General41

15.2	Protection of wiring	41
15.3	Splices and connections	42
16	Heating Elements	43
17	Electrical Insulation	43
18	Thermal Insulation	44
19	Capacitors	44
20	Lampholders	45
21	Motors	45
21.1	General	45
21.2	Overload protection	45
21.3	Insulation systems	47
22	Overcurrent Protective Devices	48
23	Receptacles	48
24	Switches and Controls	48
25	Controls – End Product Test Parameters	49
25.1	General	49
25.2	Auxiliary controls	49
25.3	Operating controls (regulating controls)	49
25.4	Protective controls (limiting controls)	50
25.5	Controls using a temperature sensing device	52
26	Spacings	52

PROTECTION AGAINST INJURY TO PERSONS

27	General	53
28	Parts Subject to Pressure	54
29	Pressure Relief Devices	55

PERFORMANCE

30	General	56
31	Leakage Current Test	56
32	Test of Insulation Resistance and Leakage Current as a Result of Moisture	59
33	Input Test	60
34	Temperature Test	60
34.1	General	60
34.2	Maximum normal load	65
34.3	Appliances with thermostatically-controlled heated ironing surfaces	65
34.4	Appliances with nonthermostatically-controlled heated ironing surfaces	65
34.5	Parts near handle	65
35	Dielectric Voltage-Withstand Test	67
36	Mechanical Endurance Test	67
37	Abnormal Operation Test	67
37.1	General	67
37.2	Water droplet test	68
37.3	Dual voltage appliances	68
37.4	Overfill test	69
37.5	Components	69
38	Tests on Switches and Control Devices	69
38.1	Overload	69
38.2	Endurance	70
39	Strain Relief Test	71
40	Polymeric Material Tests	71
40.1	General	71
40.2	Mold-stress evaluation	71
40.3	Flame resistance	72

40.4	Mechanical abuse test	72
41	Test of Physical Properties of a Liquid Container, Seal, or Diaphragm.....	72
42	Permanence of Marking.....	73
42.2	Oven-aging test.....	74
42.3	Immersion test.....	74
42.4	Standard-atmosphere test.....	74
42.5	Unusual-condition exposure test.....	74
43	Thermoplastic Motor Insulation Systems	75
43.1	General.....	75
43.2	Abnormal conditioning.....	75
43.3	Abnormal conditioning.....	75
43.4	Thermal aging	76
44	Solenoids	78
45	General Purpose Transformers	78
45.1	General.....	78
45.2	Voltage measurement test.....	78
45.3	Overload test.....	79
45.4	Repeated dielectric voltage-withstand test.....	79

MANUFACTURING AND PRODUCTION TESTS

46	Dielectric Voltage-Withstand Test	79
47	Grounding Continuity Test.....	80

RATING

48	Details.....	81
----	--------------	----

MARKING

49	Details.....	81
49.1	General.....	81
49.2	Dual voltage appliances	82
50	Instruction Manual.....	83

ELECTRODE-TYPE GARMENT FINISHING APPLIANCES

51	Scope.....	84
52	General	84
53	Construction	85
54	Normal Temperature Test.....	85
55	Abnormal Operation Test	85
56	Leakage Current Test	86
57	Disassembly and Reassembly Test.....	86
58	Markings.....	87
59	Operating Instructions.....	87

GARMENT FINISHING MACHINES EMPLOYING IONIZATION TECHNOLOGY

60	General	87
61	Glossary.....	87
62	Construction	87
63	Ozone Test	88

No Text on This Page

[ULNORM.COM](https://ulnorm.com) : Click to view the full PDF of UL 141 2025

INTRODUCTION

1 Scope

1.1 These requirements cover electric garment finishing appliances rated 250 V or less for household and commercial use, in accordance with the National Electrical Code, NFPA 70.

1.2 These requirements do not apply to flatirons, dry-cleaning machines, laundry equipment, revolving clothes racks, or other appliances covered by individual requirements that are separate from this standard.

2 Glossary

2.1 For the purpose of these requirements, the following definitions apply.

2.2 **APPLIANCE COUPLER** – A single-outlet, female contact device for attachment to a flexible cord as part of a detachable power-supply cord to be connected to an appliance inlet (motor attachment plug).

2.3 **APPLIANCE INLET (MOTOR ATTACHMENT PLUG)** – A male contact device mounted on an end product appliance to provide an integral blade configuration for the connection of an appliance coupler or cord connector.

2.4 **APPLIANCE (FLATIRON) PLUG** – An appliance coupler type of device having a cord guard and a slot configuration specified for use with heating or cooking appliances.

2.5 **COMPONENT** – A device or fabricated part of the appliance covered by the scope of a safety standard dedicated to the purpose. When incorporated in an appliance, equipment otherwise typically field installed (e.g. luminaire) is considered to be a component. Unless otherwise specified, materials that compose a device or fabricated part, such as thermoplastic or copper, are not considered components.

2.6 **CORD CONNECTOR** – A female contact device wired on flexible cord for use as an extension from an outlet to make a detachable electrical connection to an attachment plug or, as an appliance coupler, to an equipment inlet.

2.7 **CONTROL, AUTOMATIC ACTION** – A control in which at least one aspect is non-manual.

2.8 **CONTROL, AUXILIARY** – A device or assembly of devices that provides a functional utility, is not relied upon as an operational or protective control, and therefore is not relied upon for safety. For example, an efficiency control not relied upon to reduce the risk of electric shock, fire, or injury to persons during normal or abnormal operation of the end product is considered an auxiliary control.

2.9 **CONTROL, MANUAL** – A device that requires direct human interaction to activate or rest the control.

2.10 **CONTROL OPERATING** – A device or assembly of devices, the operation of which starts or regulates the end product during normal operation. For example, a thermostat, the failure of which a thermal cutout/limiter or another layer of protection would reduce the risk of electric shock, fire, or injury to persons, is considered an operating control.

2.11 **CONTROL, PROTECTIVE** – A device or assembly of devices, the operation of which is intended to reduce the risk of electric shock, fire or injury to persons during normal and reasonably anticipated abnormal operation of the appliance. For example, a thermal cutout/limiter, or any other control/circuit relied upon for normal and abnormal conditions, is considered a protective control. (During the testing of the protective control/circuit, the protective functions are verified under normal and single-fault conditions of the control.)

2.12 CONTROL, TYPE 1 ACTION – The actuation of an automatic control for which the manufacturing deviation and the drift (tolerance before and after certain conditions) of its operating value, operating time, or operating sequence has not been declared and tested under this standard.

2.13 CONTROL, TYPE 2 ACTION – The actuation of an automatic control for which the manufacturing deviation and the drift (tolerance before and after certain conditions) of its operating value, operating time, or operating sequence have been declared and tested under this standard.

2.14 HAND-SUPPORTED APPLIANCE – An appliance that is physically supported by the hand of the user during the performance of its intended functions. Reference is to be made to the instruction manual of the appliance in establishing the intended electrically operated functions of the appliance.

2.15 HARD WATER SOLUTION – A solution that consists of distilled water and sodium chloride (NaCl) with a resistivity of 1000 Ω -cm. The resistivity is adjusted by the amount of sodium chloride added.

2.16 LINE-VOLTAGE CIRCUIT – A circuit involving a potential of not more than 250 V and having circuit characteristics in excess of those of a low-voltage circuit.

2.17 LOW-VOLTAGE CIRCUIT – A circuit involving a peak open-circuit potential of not more than 42.4 V supplied by a primary battery, by a Class 2 transformer, or by a combination of a transformer and a fixed impedance that, as a unit, complies with all performance requirements for a Class 2 transformer. A circuit derived from a line-voltage circuit by connecting a resistance in series with the supply circuit as a means of limiting the voltage and current, is not considered to be a low-voltage circuit.

2.18 REMOTELY CONTROLLED APPLIANCE – An appliance that is not within sight of the operator at the starting device.

3 General

3.1 Units of measurement

3.1.1 Values stated without parentheses are the requirement. Values in parentheses are explanatory or approximate information.

3.2 Undated references

3.2.1 Any undated reference to a code or standard appearing in the requirements of this standard shall be interpreted as referring to the latest edition of that code or standard.

CONSTRUCTION

4 General

4.1 An appliance shall employ materials found by investigation to be acceptable for the intended application.

5 Components

5.1 General

5.1.1 A component of a product covered by this standard shall:

- a) Comply with the requirements for that component as indicated in [5.2](#) – [5.26](#);

- b) Be used in accordance with its rating(s) established for the intended conditions of use;
- c) Be used within its established use limitations or conditions of acceptability;
- d) Additionally comply with the applicable requirements of this end product standard; and
- e) Not contain mercury, with the exception of fluorescent lamps.

Exception No. 1: A component of a product covered by this standard is not required to comply with a specific component requirement that:

- a) Involves a feature or characteristic not required in the application of the component in the product;*
- b) Is superseded by a requirement in this end product standard; or*
- c) Is separately investigated when forming part of another component, provided the component is used within its established ratings and limitations.*

Exception No. 2: A component that complies with a UL component standard other than those specified in [5.2](#) – [5.26](#) is acceptable if:

- a) The component also complies with the applicable component standard of [5.2](#) – [5.26](#); or*
- b) The UL component standard:
 - 1) Is compatible with the ampacity and overcurrent protection requirements National Electrical Code, NFPA 70, where applicable;*
 - 2) Considers long-term thermal properties of polymeric insulating materials in accordance with the Standard for Polymeric Materials – Long Term Property Evaluations, UL 746B; and*
 - 3) Any use limitations of the other component standard are identified and appropriately accommodated in the end use application. For example, a component used in a household application, but intended for industrial use and complying with the relevant component standard may assume user expertise not common in household applications.**

5.1.2 A component that is also intended to perform other functions, such as over current protection, ground-fault circuit-interruption, surge suppression, any other similar functions, or any combination thereof, shall comply additionally with the requirements of the applicable UL standard(s) that cover devices that provide those functions.

Exception: Where these other functions are not required for the application and not identified as part of markings, instructions, or packaging for the appliance, the additional UL component standard(s) need not be applied.

5.1.3 A component not anticipated by the requirements of this end product standard, not specifically covered by the component standards in [5.2](#) – [5.26](#), and that involves a risk of electric shock, fire, or personal injury, shall be additionally investigated in accordance with the applicable UL standard, and shall comply with items (b) – (e) of [5.1.1](#).

5.1.4 With regard to [5.1.3](#), reference to construction and performance requirements in another UL end product standard is appropriate where that standard anticipates normal and abnormal use conditions consistent with the application of the requirements of this end product standard.

5.1.5 Specific components are incomplete in construction features or restricted in performance capabilities. Such components are intended for use only under limited conditions, such as certain temperatures not exceeding specified limits, and shall be used only under those specific conditions.

5.2 Attachment plugs, receptacles, connectors, and terminals

5.2.1 Attachment plugs, receptacles, appliance couplers, appliance inlets (motor attachment plugs), and appliance (flatiron) plugs, shall comply with the Standard for Attachment Plugs and Receptacles, UL 498.

Exception: Attachment plugs and appliance couplers integral to cord sets or power supply cords that are investigated in accordance with the requirements of the Standard for Cord Sets and Power-Supply Cords, UL 817 and need not comply with the Standard for Attachment Plugs and Receptacles, UL 498.

5.2.2 Quick-connect terminals, both connectors and tabs, for use with one or two 22–10 AWG copper conductors, having nominal widths of 2.8, 3.2, 4.8, 5.2, and 6.3 mm (0.110, 0.125, 0.187, 0.205, and 0.250 in), intended for internal wiring connections in appliances, or for the field termination of conductors to the appliance, shall comply with the Standard for Electrical Quick-Connect Terminals, UL 310.

Exception: Other sizes of quick-connect terminals shall be investigated with respect to crimp pull out, insertion-withdrawal, temperature rise, and all tests shall be conducted in accordance with the Standard for Electrical Quick-Connect Terminals, UL 310.

5.2.3 Single and multi-pole connectors for use in data, signal, control and power applications within and between electrical equipment, and that are intended for factory assembly to copper or copper alloy conductors, or for factory assembly to printed wiring boards, shall comply with the Standard for Component Connectors for Data, Signal, Control and Power Applications, UL 1977.

5.2.4 Wire connectors shall comply with the Standard for Wiring Connectors, UL 486A-486B.

5.2.5 Splicing wire connectors shall comply with the Standard for Splicing Wire Connectors, UL 486C.

5.2.6 Multi-pole splicing wire connectors that are intended to facilitate the connection of hard-wired utilization equipment to the branch-circuit conductors of buildings shall comply with the Standard for Multi-Pole Splicing Wire Connectors, UL 2459.

5.2.7 Equipment wiring terminals for use with all alloys of copper, aluminum, or copper-clad aluminum conductors, shall comply with Standard for Equipment Wiring Terminals for Use with Aluminum and/or Copper Conductors, UL 486E.

5.2.8 Terminal blocks shall comply with the Standard for Terminal Blocks, UL 1059, and, if applicable, be suitably rated for field wiring.

Exception: A fabricated part performing the function of a terminal block need not comply with the Standard for Terminal Blocks, UL 1059 if the part complies with the requirements of Wiring Terminals and Leads, [12.1.3](#); Current-Carrying Parts, Section [14](#); Electrical Insulation, Section [17](#); and Spacings, Section [26](#) of this end product standard.

5.2.9 Female devices (such as receptacles, appliance couplers, and connectors) that are intended, or that may be used, to interrupt current in the end product, shall be suitably rated for current interruption of the specific type of load, when evaluated with its mating plug or connector. For example, an appliance coupler that can be used to interrupt the current of a motor load shall have a suitable horsepower rating when tested with its mating plug.

5.3 Batteries and battery chargers

5.3.1 A lithium ion (Li-On) single cell battery shall comply with the requirements for secondary lithium cells in the Standard for Lithium Batteries, UL 1642. A lithium ion multiple cell battery and a lithium ion battery pack shall comply with the applicable requirements for secondary lithium cells or battery packs in the Standard for Household and Commercial Batteries, UL 2054.

5.3.2 Rechargeable nickel cadmium (Ni-Cad) cells and battery packs shall comply with the applicable construction and performance requirements of this end product standard.

5.3.3 Rechargeable nickel metal-hydride (Ni-MH) battery cells and packs shall comply with the applicable construction and performance requirements of this end product standard, or the applicable requirements for secondary cells or battery packs in the Standard for Household and Commercial Batteries, UL 2054.

5.3.4 Primary batteries (non-rechargeable) that comply with the relevant UL standard and [5.1](#) are considered to fulfill the requirements of this standard.

5.3.5 A Class 2 battery charger shall comply with one of the following:

- a) The Standard for Class 2 Power Units, UL 1310; or
- b) The Standard for Information Technology Equipment, Part 1: General Requirements, UL 60950-1 with an output marked "Class 2", or that complies with the limited power source (LPS) requirements and is marked "LPS".

5.3.6 A non-Class 2 battery charger shall comply with one of the following:

- a) The Standard for Power Units Other Than Class 2, UL 1012; or
- b) The Standard for Information Technology Equipment, Part 1: General Requirements, UL 60950-1.

5.4 Boxes and raceways

5.4.1 Electrical boxes and the associated bushings and fittings, and raceways, of the types specified in Chapter 3 of the National Electrical Code, NFPA 70 and that comply with the relevant UL standard (such as the Standard for Metallic Outlet Boxes, UL 514A, the Standard for Nonmetallic Outlet Boxes, Flush-Device Boxes, and Covers, UL 514C, the Standard for Cover Plates for Flush-Mounted Wiring Devices, UL 514D, and [5.1](#)) are considered to comply with the requirements of this end product standard.

5.5 Capacitors and filters

5.5.1 The component requirements for a capacitor are not specified. A capacitor complying with the Standard for Capacitors, UL 810, is considered to comply with the requirements of [19.1](#).

5.5.2 Electromagnetic interference filters with integral enclosures that comply with one of the following standards, are considered to comply with the requirements of [19.1](#):

- a) The Standard for Electromagnetic Interference Filters, UL 1283; or
- b) The Standard for Fixed Capacitors for Use in Electronic Equipment – Part 14: Sectional Specification: Fixed Capacitors for Electromagnetic Interference Suppression and Connection to the Supply Mains, UL 60384-14.

5.6 Controls

5.6.1 General

5.6.1.1 Auxiliary controls shall be evaluated using the applicable requirements of this end product standard and the requirements in Section [25](#).

5.6.1.2 Operating (regulating) controls shall be evaluated using the applicable component standard requirements specified in [5.6.2](#) – [5.6.7](#) and the parameters in Section [25](#), unless otherwise specified in this end product standard.

5.6.1.3 Operating controls that rely upon software for the normal operation of the end product where deviation or drift of the operating parameters of the control may result in an increased risk of electric shock, fire, or injury to persons, shall comply with:

- a) The Standard for Tests for Safety-Related Controls Employing Solid-State Devices, UL 991; and the Standard for Software in Programmable Components, UL 1998; or
- b) The Standard for Automatic Electrical Controls for Household and Similar Use; Part 1: General Requirements, UL 60730-1.

5.6.1.4 Protective (limiting) controls shall be evaluated using the applicable component standard requirements specified in [5.6.2](#) – [5.6.7](#), and if applicable, the parameters in Section [25](#), unless otherwise specified in this end product standard.

5.6.1.5 Solid-state protective controls that do not rely upon software as a protective component shall comply with:

- a) The Standard for Tests for Safety-Related Controls Employing Solid-State Devices, UL 991; or
- b) The Standard for Automatic Electrical Controls for Household and Similar Use, Part 1: General Requirements, UL 60730-1, except Controls Using Software.

5.6.1.6 Protective controls that rely upon software as a protective component shall comply with:

- a) The Standard for Tests for Safety-Related Controls Employing Solid-State Devices, UL 991; and the Standard for Software in Programmable Components, UL 1998; or
- b) The Standard for Automatic Electrical Controls for Household and Similar Use, Part 1: General Requirements, UL 60730-1, except Controls Using Software.

5.6.1.7 An electronic, non-protective control that is simple in design need only be subjected to the applicable requirements of this end-product standard. A control that does not include an integrated circuit or microprocessor, but does consist of a discrete switching device, capacitors, transistors, and resistors, is considered simple in design. See Section [37](#).

5.6.2 Electromechanical and electronic controls

5.6.2.1 A control, other than as specified in [5.6.3](#) – [5.6.7](#), shall comply with:

- a) The Standard for Solid-State Controls for Appliances, UL 244A; or
- b) The Standard for Temperature-Indicating and -Regulating Equipment, UL 873; or
- c) The Standard for Automatic Electrical Controls for Household and Similar Use, Part 1: General Requirements, UL 60730-1.

5.6.3 Liquid level controls

5.6.3.1 A liquid level control shall comply with:

- a) The Standard for Solid-State Controls for Appliances, UL 244A; or
- b) The Standard for Temperature-Indicating and -Regulating Equipment, UL 873; or
- c) The Standard for Industrial Control Equipment, UL 508; or
- d) The Standard for Automatic Electrical Controls for Household and Similar Use, Part 1: General Requirements, UL 60730-1; and
 - 1) The Standard for Automatic Electrical Controls for Household and Similar Use, Part 2: Particular Requirements for Automatic Electrical Water Level Controls of the Float Type for Household and Similar Applications, UL 60730-2-16A; or
 - 2) The Standard for Automatic Electrical Controls for Household and Similar Use, Part 2: Particular Requirements for Automatic Electrical Water and Air Flow Sensing Controls, Including Mechanical Requirements, UL 60730-2-18.

5.6.4 Motor and speed controls

5.6.4.1 A control used to start, stop, regulate or control the speed of a motor shall comply with:

- a) The Standard for Solid-State Controls for Appliances, UL 244A; or
- b) The Standard for Temperature-Indicating and -Regulating Equipment, UL 873; or
- c) The Standard for Industrial Control Equipment, UL 508; or
- d) The Standard for Adjustable Speed Electrical Power Drive Systems – Part 5-1: Safety Requirements – Electrical, Thermal, and Energy, UL 61800-5-1; or
- e) The Standard for Automatic Electrical Controls for Household and Similar Use, Part 1: General Requirements, UL 60730-1.

5.6.5 Pressure controls

5.6.5.1 A pressure control shall comply with one of the following:

- a) The Standard for Temperature-Indicating and -Regulating Equipment, UL 873; or
- b) The Standard for Industrial Control Equipment, UL 508; or
- c) The Standard for Automatic Electrical Controls for Household and Similar Use, Part 1: General Requirements, UL 60730-1; and the Standard for Automatic Electrical Controls for Household and Similar Use, Part 2: Particular Requirements for Automatic Electrical Pressure Sensing Controls Including Mechanical Requirements, UL 60730-2-6.

5.6.6 Temperature controls

5.6.6.1 A temperature control shall comply with:

- a) The Standard for Solid-State Controls for Appliances, UL 244A; or
- b) The Standard for Temperature-Indicating and -Regulating Equipment, UL 873; or

- c) The Standard for Industrial Control Equipment, UL 508; or
- d) The Standard for Automatic Electrical Controls for Household and Similar Use, Part 1: General Requirements, UL 60730-1; and the Standard for Automatic Electrical Controls for Household and Similar Use, Part 2: Particular Requirements for Temperature Sensing Controls, UL 60730-2-9.

5.6.6.2 A temperature sensing positive temperature coefficient (PTC) or a negative temperature coefficient (NTC) thermistor, that performs the same function as an operating or protective control shall comply with the Standard for Thermistor-Type Devices, UL 1434.

5.6.6.3 A thermal cutoff shall comply with the Standard for Thermal-Links (Thermal Cutoffs) for Use in Electrical Appliances and Components, UL 60691.

5.6.7 Timer controls

5.6.7.1 A timer control shall comply with:

- a) The Standard for Solid-State Controls for Appliances, UL 244A; or
- b) The Standard for Automatic Electrical Controls for Household and Similar Use, Part 1: General Requirements, UL 60730-1; and the Standard for Automatic Electrical Controls for Household and Similar Use, Part 2: Particular Requirements for Timers and Time Switches, UL 60730-2-7.

5.7 Cords, cables, and internal wiring

5.7.1 A cord set or power supply cord shall comply with the Standard for Cord Sets and Power Supply Cords, UL 817.

5.7.2 Flexible cords and cables shall comply with the Standard for Flexible Cords and Cables, UL 62. Flexible cord and cables are considered to fulfill this requirement when preassembled in a cord set or power supply cord complying with the Standard for Cord Sets and Power Supply Cords, UL 817.

5.7.3 Internal wiring composed of insulated conductors shall comply with the Standard for Appliance Wiring Material, UL 758.

Exception No. 1: Insulated conductors need not comply with the Standard for Appliance Wiring Material, UL 758 if they comply with one of the following:

- a) *The Standard for Thermoset-Insulated Wires and Cables, UL 44;*
- b) *The Standard for Thermoplastic-Insulated Wires and Cables, UL 83;*
- c) *The Standard for Fixture Wire, UL 66; or*
- d) *The applicable UL standard(s) for other insulated conductor types specified in Chapter 3 (Wiring Methods and Materials) of the National Electrical Code, NFPA 70.*

Exception No. 2: Insulated conductors for specialty applications (e.g. data processing or communications) and located in a low-voltage circuit not involving the risk of fire or personal injury need not comply with the Standard for Appliance Wiring Material, UL 758

5.8 Cord reels

5.8.1 A cord reel shall comply with special use cord reel requirements of the Standard for Cord Reels, UL 355.