



UL 19

STANDARD FOR SAFETY

Lined Fire Hose and Hose Assemblies

[ULNORM.COM](https://www.ulnorm.com) : Click to view the full PDF of UL 19 2024

ULNORM.COM : Click to view the full PDF of UL 19 2024

UL Standard for Safety for Lined Fire Hose and Hose Assemblies, UL 19

Fourteenth Edition, Dated August 13, 2018

SUMMARY OF TOPICS

This revision of ANSI/UL 19 dated February 2, 2024 includes the following changes in requirements:

– Additional Fire Hose Trade Sizes, Internal and Outside Diameter Requirements, Additional Hose Pressure Options, Product Specification Sheet Requirements, and Other Clarifications/Corrections; [1.1](#), [4.1A](#), [4.3](#), [Section 5A](#), [11.1.1](#), [Table 11.1](#), [14.1.1](#), [Table 14.1](#), [Table 14.2](#), [16.1.1](#), [16.3.1](#), [17.4.1](#), [Table 22.1](#), [22.2.1](#), [27.5.1](#), [37.1.3](#), [37.2.3](#), [37.4.7](#), [37.5.2](#), [38.1.2](#), [38.2.3](#), [38.4.1](#), [38.4.3](#), [38.5.2](#), [Section 38A](#), [39.2](#), [Section 41](#) and [C.3.1](#)

– Editorial revisions; [Section 3](#), [10.2](#), [11.1.1](#), [16.3.1](#), [18.3.1](#), [22.3.1](#), [23.3.1](#), [25.3.1](#), [25.3.4](#), [25.3.5](#), [25.3.6](#), [25.4.1](#), [25.4.3](#), [25.4.7](#), [26.3.1](#), [27.1.1](#), [27.4.1](#), [31.4.1](#), [32.1.1](#), [32.3.1](#), [32.4.1](#), [32.4.2](#), [34.2.1](#), [34.3.1](#), [34.4.1](#) and [40.2.1](#)

Text that has been changed in any manner or impacted by ULSE's electronic publishing system is marked with a vertical line in the margin.

The new and revised requirements are substantially in accordance with Proposal(s) on this subject dated August 25, 2023 and December 22, 2023.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of ULSE Inc. (ULSE).

ULSE provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will ULSE be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if ULSE or an authorized ULSE representative has been advised of the possibility of such damage. In no event shall ULSE's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold ULSE harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 19 2024

AUGUST 13, 2018
(Title Page Reprinted: February 2, 2024)



ANSI/UL 19-2024

1

UL 19

Standard for Lined Fire Hose and Hose Assemblies

The First through Sixth editions were titled "Cotton Rubber-Lined Hose."

Fifth Edition – April, 1948
Sixth Edition – August, 1953
Seventh Edition – August, 1967
Eighth Edition – October, 1971
Ninth Edition – March, 1978
Tenth Edition – December, 1992
Eleventh Edition – December, 1995
Twelfth Edition – November, 2001
Thirteenth Edition – October, 2013

Fourteenth Edition

August 13, 2018

This ANSI/UL Standard for Safety consists of the Fourteenth Edition including revisions through February 2, 2024.

The most recent designation of ANSI/UL 19 as an American National Standard (ANSI) occurred on February 2, 2024. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, and Title Page.

The Department of Defense (DoD) has adopted UL 19 on April 5, 1999. The publication of revised pages or a new edition of this Standard will not invalidate the DoD adoption.

Comments or proposals for revisions on any part of the Standard may be submitted to ULSE at any time. Proposals should be submitted via a Proposal Request in ULSE's Collaborative Standards Development System (CSDS) at <https://csds.ul.com>.

Our Standards for Safety are copyrighted by ULSE Inc. Neither a printed nor electronic copy of a Standard should be altered in any way. All of our Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of ULSE Inc.

COPYRIGHT © 2024 ULSE INC.

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 19 2024

CONTENTS

INTRODUCTION

1	Scope	7
2	Units of Measurement	7
3	Referenced Publications	7
4	Glossary	8

CONSTRUCTION

5	Diameter	8
5A	Diameter of Hose	8
	5A.1 Internal diameter of uncharged hose	8
	5A.2 Internal diameter of charged hose	9
	5A.3 Outside diameter of charged hose	9
6	Jacket and Inner Reinforcements	9
7	Lining	9
8	Cover	9
9	Coatings and Treatments	9
10	Couplings	10

PERFORMANCE

11	Hydrostatic Proof-Pressure Tests	10
	11.1 General	10
	11.2 Sample	11
	11.3 Equipment	11
	11.4 Test method	11
12	Kink Test	13
	12.1 General	13
	12.2 Sample	13
	12.3 Equipment	13
	12.4 Test method	13
13	Hydrostatic Strength Test	13
	13.1 General	13
	13.2 Sample	13
	13.3 Equipment	13
	13.4 Test method	14
14	Repeated Bending Test	14
	14.1 General	14
	14.2 Sample	14
	14.3 Equipment	15
	14.4 Test method	15
15	Alternating Pressure Test	15
	15.1 General	15
	15.2 Sample	15
	15.3 Equipment	16
	15.4 Test method	16
16	Abrasion Test	16
	16.1 General	16
	16.2 Sample	16
	16.3 Equipment	16
	16.4 Test method	17
17	Heat-Resistance Test	17

	17.1 General.....	17
	17.2 Sample	17
	17.3 Equipment	17
	17.4 Test method	17
18	Fold-Resistance Test.....	17
	18.1 General.....	17
	18.2 Sample	18
	18.3 Equipment	18
	18.4 Test method	18
19	Wet Hose Test.....	18
	19.1 General.....	18
	19.2 Sample	18
	19.3 Test method	18
20	Low-Temperature Test.....	18
	20.1 General.....	18
	20.2 Sample	18
	20.3 Equipment	19
	20.4 Test method	19
21	Coupling Retention Test.....	19
	21.1 General.....	19
	21.2 Sample	19
	21.3 Equipment	19
	21.4 Test method	19
22	Friction Loss Test	19
	22.1 General.....	19
	22.2 Sample	20
	22.3 Equipment	20
	22.4 Test method	20
23	Accelerated Aging Test of Threads	21
	23.1 General.....	21
	23.2 Sample	21
	23.3 Equipment	21
	23.4 Test method	21
24	Adhesion Tests.....	21
	24.1 General.....	21
	24.2 Sample	22
	24.3 Equipment	22
	24.4 Test method	22
25	Accelerated Aging Test of Linings and Covers	22
	25.1 General.....	22
	25.2 Sample	22
	25.3 Equipment	23
	25.4 Test method	23
26	Ozone-Exposure Test of Linings and Covers	24
	26.1 General.....	24
	26.2 Sample	24
	26.3 Equipment	24
	26.4 Test method	24
27	Water Immersion Test of Linings	24
	27.1 General.....	24
	27.2 Sample	25
	27.3 Equipment	25
	27.4 Method – Effect on tensile strength and ultimate elongation	25
	27.5 Method – Effect on volume	25
28	Pull Test.....	26
	28.1 General.....	26

28.2	Sample	26
28.3	Test method	26
29	Accelerated Aging Test of Hose Assembly.....	26
29.1	General.....	26
29.2	Sample	26
29.3	Equipment	26
29.4	Test method	26
30	Rough Usage Test.....	26
30.1	General.....	26
30.2	Sample	27
30.3	Equipment	27
30.4	Test method	27
31	Moist Ammonia-Air Stress Cracking Test.....	27
31.1	General.....	27
31.2	Sample	27
31.3	Equipment	27
31.4	Method	27
32	Salt-Spray Corrosion Test	28
32.1	General.....	28
32.2	Sample	28
32.3	Equipment	28
32.4	Test method	28
33	Accelerated Aging Test of Gaskets	28
33.1	General.....	28
33.2	Sample	28
33.3	Equipment	29
33.4	Test method	29
34	Compression Set Test.....	29
34.1	General.....	29
34.2	Samples	29
34.3	Equipment	29
34.4	Test method	29
35	Ozone Resistance Test of Gaskets	29
35.1	General.....	29
35.2	Sample	29
35.3	Equipment	29
35.4	Test method	30
36	Water Immersion Test of Gaskets	30
36.1	General.....	30
36.2	Sample	30
37	Radiant Heat Test.....	30
37.1	General.....	30
37.2	Samples	30
37.3	Equipment	31
37.4	Test method	31
37.5	Radiant heat test results	32
38	Conductive Heat Test.....	33
38.1	General.....	33
38.2	Samples	33
38.3	Equipment	34
38.4	Test method	34
38.5	Conductive heat test results.....	34
38A	Diameter of Charged Hose Tests.....	35
38A.1	General	35
38A.2	Samples	35
38A.3	Equipment	35

[www.ul.com](#) . Click to view the full PDF of UL 19 2024

38A.4 Method	35
38A.5 Reported Results.....	36

MANUFACTURING AND PRODUCTION TESTS

39 General	36
------------------	----

MARKING

40 Details.....	36
40.1 General.....	36
40.2 Hose.....	36
40.3 Hose assemblies	37

PRODUCT SPECIFICATION SHEET

41 General	37
------------------	----

Appendix A – (Informative) – Example Radiant Heat Test Apparatus

A.1 General	39
A.2 Support Frame.....	39
A.3 Stainless Steel Heating Element	39
A.4 Premixed Flow Control	42
A.5 Heater Traverse	42
A.6 Heat Flux Gauge.....	42
A.7 Sensing Surface	42
A.8 Gauge Position	43

Appendix B – (Informative) – Conductive Heat Test Apparatus

B.1 General.....	44
------------------	----

Appendix C – (Informative) – Radiant Heat and Conductive Heat Test Results

C.1 General.....	49
C.2 Radiant Heat and Conductive Heat Test Results.....	49
C.3 History on Method Development and Choice of Parameters	49

INTRODUCTION

1 Scope

1.1 These requirements cover single- and multiple-jacketed lined fire hose with or without couplings attached, in the trade sizes of 1-1/2, 1-3/4, 2, 2-1/4, 2-1/2, 2-3/4, 3, 3-1/2, 4, 4-1/2, 5, and 6 inch (38, 45, 51, 57, 65, 70, 76, 89, 102, 114, 127, and 152 mm nominal ID). Single-jacketed hose is intended for service test pressures of 150 psig (1035 kPa) and above in 25 psig (170 kPa) increments. Multiple-jacketed hose or covered hose judged equivalent to multiple-jacketed hose is intended for service test pressures of 200 psig (1380 kPa) and above in 25 psig (170 kPa) increments.

1.2 These products are intended for municipal and industrial fire protection purposes. Single-jacketed hose is for use at fire hydrants, standpipes, and similar places. They are not intended for hard usage nor where the hose will be subjected to chafing on rough or sharp surfaces. Multiple-jacketed hose or covered hose judged equivalent to multiple-jacketed hose are for use on pumpers and in places where service conditions require the additional protection against wear afforded by the extra woven jacket or cover.

1.3 The products covered by these requirements are intended to be periodically inspected and maintained while in service, as outlined in the Standard for the Care, Use, Inspection, Service Testing and Replacement of Fire Hose, Couplings, Nozzles, and Fire Hose Appliances, NFPA 1962.

2 Units of Measurement

2.1 Values stated without parentheses are the requirement. Values in parentheses are explanatory or approximate information.

3 Referenced Publications

3.1 Any undated reference to a code or standard appearing in the requirements of this Standard shall be interpreted as referring to the latest edition of that code or standard.

3.2 The following publications are referenced in this Standard:

ASTM B30, *Standard Specification for Copper Alloys in Ingot and Other Remelt Forms*

ASTM B117, *Standard Practice for Operating Salt Spray (Fog) Apparatus*

ASTM B584, *Standard Specification for Copper Alloy Sand Castings for General Applications*

ASTM D395, *Standard Test Methods for Rubber Property – Compression Set*

ASTM D412, *Standard Test Methods for Vulcanized Rubber and Thermoplastic Elastomers – Tension*

ASTM D573, *Standard Test Method for Rubber – Deterioration in an Air Oven*

ASTM D1149, *Standard Test Methods for Rubber Deterioration – Cracking in an Ozone Controlled Environment*

ASTM D3183, *Standard Practice for Rubber – Preparation of Pieces for Test Purposes from Products*

ASTM E145, *Standard Specification for Gravity-Convection and Forced-Ventilation Ovens*

NFPA 1961, *Standard on Fire Hose*