



UL 2420

STANDARD FOR SAFETY

Belowground Reinforced Thermosetting Resin Conduit (RTRC) and Fittings

ULNORM.COM : Click to view the full PDF of UL 2420 2021

ULNORM.COM : Click to view the full PDF of UL 2420 2021

UL Standard for Safety for Belowground Reinforced Thermosetting Resin Conduit (RTRC) and Fittings, UL 2420

First Edition, Dated July 30, 2009

Summary of Topics

This revision of ANSI/UL 2420 dated April 30, 2021 includes the following:

– Clarification on where to measure the minimum inside diameter of socket specified in [Table 5](#) to [Table 8](#)

– Editorial updates to replace the reference to “CEC” with “CE Code”; [1.1](#), [2.4](#) and [3.1.1](#)

Text that has been changed in any manner or impacted by UL's electronic publishing system is marked with a vertical line in the margin.

The revised requirements are substantially in accordance with Proposal (s) on this subject dated December 18, 2020.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of UL.

UL provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will UL be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if UL or an authorized UL representative has been advised of the possibility of such damage. In no event shall UL's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold UL harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 2420 2021



Canadian Standards Association
CSA C22.2 No. 2420-09
First Edition



Underwriters Laboratories Inc.
UL 2420
First Edition

Belowground Reinforced Thermosetting Resin Conduit (RTRC) and Fittings

July 30, 2009

(Title Page Reprinted: April 30, 2021)

ULNORM.COM : Click to view the full PDF of UL 2420-2021



ANSI/UL 2420-2021



Commitment for Amendments

This standard is issued jointly by the Canadian Standards Association (operating as “CSA Group”) and Underwriters Laboratories Inc. (UL). Comments or proposals for revisions on any part of the standard may be submitted to CSA Group or UL at anytime. Revisions to this standard will be made only after processing according to the standards development procedures of CSA Group and UL. CSA Group and UL will issue revisions to this standard by means of a new edition or revised or additional pages bearing their date of issue.

ISBN 1-55397-056-X © 2014 Canadian Standards Association

All rights reserved. No part of this publication may be reproduced in any form whatsoever without the prior permission of the publisher.

This Standard is subject to review within five years from the date of publication, and suggestions for its improvement will be referred to the appropriate committee. To submit a proposal for change, please send the following information to inquiries@csagroup.org and include "Proposal for change" in the subject line: Standard designation (number); relevant clause, table, and/or figure number; wording of the proposed change; and rationale for the change.

To purchase CSA Group Standards and related publications, visit CSA's Online Store at www.csagroup.org/store/ or call toll-free 1-800-463-6727 or 416-747-4044.

Copyright © 2021 Underwriters Laboratories Inc.

UL's Standards for Safety are copyrighted by UL. Neither a printed nor electronic copy of a Standard should be altered in any way. All of UL's Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of UL.

This ANSI/UL Standard for Safety consists of the First Edition including revisions through April 30, 2021.

The most recent designation of ANSI/UL 2420 as an American National Standard (ANSI) occurred on April 30, 2021. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, Title Page (front and back), or the Preface.

Comments or proposals for revisions on any part of the Standard may be submitted to UL at any time. Proposals should be submitted via a Proposal Request in UL's On-Line Collaborative Standards Development System (CSDS) at <https://csds.ul.com>.

To purchase UL Standards, visit UL's Standards Sales Site at <http://www.shopulstandards.com/HowToOrder.aspx> or call toll-free 1-888-853-3503.

CONTENTS

PREFACE	5
1 Scope	7
2 Definitions	7
3 Reference publications and units of measurement	7
3.1 Reference publications	7
3.2 Units of measurement	8
4 Construction	8
4.1 General	8
4.2 Conduit with an integral belled end	8
4.3 Couplings	8
4.4 Elbows	8
4.5 Adapters	9
5 Qualification tests	9
5.1 Conditioning	9
5.2 Compression	9
5.3 Impact resistance at low temperature	10
5.4 Water absorption	10
5.5 Chemical resistance (optional)	11
5.6 Watertightness	12
5.7 Joint separation	12
5.8 Flattening resistance	13
5.9 Halogen content	13
5.10 Infrared spectroscopy	13
5.11 Tensile strength	14
5.12 Durability of printing (all types with surface-applied markings of ink, dyes, etc.)	14
6 Marking	14
Annex A (Normative) Method to determine the halogen content of a low-halogen material using the calculation method from pH and acid gas evolution	
A.1 General	28
A.2 Test equipment	28
A.2.1 General	28
A.2.2 Equipment layout	28
A.3 Test procedure	29
A.3.1 Sample preparation	29
A.3.2 Apparatus assembly	29
A.3.3 Acid gas evolution	30
A.3.4 Acid gas measurement	30
Annex B (informative) Rationale for threaded adapter dimensions for size 4-1/2 (116)	