



UL 391

STANDARD FOR SAFETY

Solid-Fuel and Combination-Fuel
Central and Supplementary Furnaces

ULNORM.COM : Click to view the full PDF of UL 391 2024

ULNORM.COM : Click to view the full PDF of UL 391 2024

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

UL Standard for Safety for Solid-Fuel and Combination-Fuel Central and Supplementary Furnaces, UL 391

Sixth Edition, Dated October 21, 2024

Summary of Topics

This sixth edition of ANSI/UL 391 dated October 21, 2024 includes updated Referenced Publications, Section 4, Conversion correction, [53.2.1](#); and Editorial updates throughout the Standard.

The requirements are substantially in accordance with Proposal(s) on this subject dated July 12, 2024 and August 23, 2024.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of ULSE Inc. (ULSE).

ULSE provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will ULSE be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if ULSE or an authorized ULSE representative has been advised of the possibility of such damage. In no event shall ULSE's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold ULSE harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

ULNORM.COM : Click to view the full PDF of UL 391 2024

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 391 2024

OCTOBER 21, 2024



ANSI/UL 391-2024

1

UL 391

Standard for Solid-Fuel and Combination-Fuel Central and Supplementary

Furnaces

First Edition – July, 1981
Second Edition – August, 1991
Third Edition – April, 1995
Fourth Edition – October, 2006
Fifth Edition – September, 2010

Sixth Edition

October 21, 2024

This ANSI/UL Standard for Safety consists of the Sixth Edition.

The most recent designation of ANSI/UL 391 as an American National Standard (ANSI) occurred on October 21, 2024. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, and Title Page.

Comments or proposals for revisions on any part of the Standard may be submitted to ULSE at any time. Proposals should be submitted via a Proposal Request in the On-Line Collaborative Standards Development System (CSDS) at <https://csds.ul.com>

Our Standards for Safety are copyrighted by ULSE Inc. Neither a printed nor electronic copy of a Standard should be altered in any way. All of our Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of ULSE Inc.

© 2024 ULSE Inc. All rights reserved.

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 391 2024

CONTENTS

INTRODUCTION

1	Scope	7
2	Components	7
3	Units of Measurement	7
4	Referenced Publications	8
5	Glossary	8

CONSTRUCTION

6	General	10
7	Accessibility for Servicing	13
8	Protection of Users and Service Personnel	13
9	Base	16
10	Casings	16
11	Radiation Shields or Liners	17
12	Materials in Air-Handling Compartments	17
13	Air Filters	18
14	Combustion Chambers	18
15	Radiators	18
16	Heating Surface Joints	18
17	Baffles	19
18	Flue Collars	19
19	Disposal of Combustion Products	20
20	Dampers, Shutters and Draft Regulators	20
21	Electrical Enclosures	20
	21.1 General	20
	21.2 Doors and covers	23
	21.3 Field wiring system connections	25
22	Accessibility of Uninsulated Live Parts, Film-Coated Wire and Moving Parts	25

FIELD WIRING

23	General	30
24	Leads and Terminals	32

INTERNAL WIRING

25	General	33
26	Methods	33
27	Short-Circuit Protection	36
28	Separation of Circuits	37
29	Bonding for Grounding	38

ELECTRICAL COMPONENTS

30	General	41
31	Mounting of Electrical Components	41
32	Electrical Insulating Material	42
33	Capacitors	42
34	Receptacles	42
35	Motors and Motor (Overload) Protection	43

36	Safety Controls and Circuits	47
36.1	General.....	47
36.2	Fan, limit, and thermostatic damper controls	47
36.3	Supplementary central furnace controls.....	48
36.4	Primary safety control	48
37	Switches and Controllers	48

SPACINGS

38	High-Voltage Circuits	49
39	Low-Voltage Circuits.....	50

PERFORMANCE

40	General	51
----	---------------	----

TEST INSTALLATION FOR CENTRAL FURNACES

41	Enclosure	51
42	Chimney Connector.....	52
43	Supply-and Return-Air Plenums and Ducts – Forced-Air Furnace	54

TEST INSTALLATION FOR SUPPLEMENTARY CENTRAL FURNACES

44	General	56
----	---------------	----

INSTRUMENTATION

45	Draft.....	56
46	Fuel Input	57
47	Power Measurement	57
48	Speed Measurement	57
49	Static Pressure.....	57
50	Temperature Measurement	59

INITIAL TEST CONDITIONS

51	General	61
52	Static Pressures for Tests.....	62
53	Solid Fuels and Test Firing Procedures	63
53.1	General.....	63
53.2	Firebrands	63
53.3	Charcoal	65

INITIAL TESTS

54	Combustion Test – Oil Burner and Furnace	66
55	Operation Test	66
56	Limit Control Cutout Test.....	67
56.1	General.....	67
56.2	Combination oil-fired and solid-fuel-fired central furnaces	67
56.3	Solid-fuel-fired central furnaces	68
56.4	Supplementary central furnaces.....	68

TEMPERATURE TESTS

57 General 69

58 Continuous Operation Test..... 73

 58.1 General..... 73

 58.2 Continuous operation..... 73

 58.3 Loss of electrical power 74

 58.4 Simultaneous firing 74

59 Air Flow Restriction and Disruption Tests..... 74

 59.1 General..... 74

 59.2 Preparatory test procedures 75

 59.3 Restricted inlet test 75

 59.4 Fan failure test..... 75

 59.5 Blocked outlet test 75

OTHER TESTS

60 Delayed Oil Ignition Test 76

61 Dielectric Voltage Withstand Test..... 76

62 Bonding Joint Test 76

63 Bonding Conductor Test..... 77

64 Knockout Security Test 77

65 Lead Stress Test 77

66 Surface Burning Test 77

67 Polymeric Materials Tests 77

 67.1 General..... 77

 67.2 Aging test..... 78

 67.3 Flammability test..... 78

68 Short Circuit Test..... 78

MANUFACTURING AND PRODUCTION TESTS

69 General 80

70 Production Line Dielectric Voltage Withstand Tests 81

MARKING

71 Nameplate 81

72 Supplementary..... 83

73 Instructions 85

Appendix A

Standards for Components 87

ULFORM.COM: Click to view the full PDF of UL 391 2024

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 391 2024

INTRODUCTION

1 Scope

1.1 These requirements apply to manually fueled, solid-fuel-fired central furnaces. Included are supplementary central furnaces intended for interconnection with forced-air central furnaces utilizing other fuels, and combination oil-fired and solid-fuel-fired, forced-air central furnaces.

1.2 The furnaces are intended to burn solid fuels, such as wood, coal, or any other biomass fuel, as specified by the manufacturer.

1.3 The furnaces are intended for connection to chimneys for residential and building heating appliances in compliance with the Standard for Chimneys, Fireplaces, Vents, and Solid Fuel Burning Appliances, NFPA 211, and intended for installation in compliance with the Standard for Installation of Warm Air Heating and Air Conditioning Systems, NFPA 90B; and the National Electrical Code, NFPA 70; and applicable mechanical codes such as the International Mechanical Code, the Standard Mechanical Code, and the Uniform Mechanical Code.

1.4 A product that contains features, characteristics, components, materials, or systems new or different from those covered by the requirements in this standard, and that involves a risk of fire or of electric shock or injury to persons shall be evaluated using appropriate additional component and end-product requirements to maintain the level of safety as originally anticipated by the intent of this standard. A product whose features, characteristics, components, materials, or systems conflict with specific requirements or provisions of this standard does not comply with this standard. Revision of requirements shall be proposed and adopted in conformance with the methods employed for development, revision, and implementation of this standard.

2 Components

2.1 Except as indicated in [2.2](#), a component of a product covered by this standard shall comply with the requirements for that component. See Appendix [A](#) for a list of standards covering components generally used in the products covered by this standard.

2.2 A component need not comply with a specific requirement that:

- a) Involves a feature or characteristic not needed in the application of the component in the product covered by this standard, or
- b) Is superseded by a requirement in this standard.

2.3 A component shall be used in accordance with its recognized rating established for the intended conditions of use.

2.4 Specific components are recognized as being incomplete in construction features or restricted in performance capabilities. Such components are intended for use only under limited conditions, such as certain temperatures not exceeding specified limits, and shall be used only under those specific conditions for which they have been recognized.

3 Units of Measurement

3.1 If a value for measurement is followed by a value in other units in parentheses, the second value may be only approximate. The first stated value is the requirement.

4 Referenced Publications

4.1 Any undated reference to a code or standard appearing in the requirements of this standard shall be interpreted as referring to the latest edition of that code or standard.

4.2 The following publications are referenced in this Standard:

ANSI C80.1, *American National Standard for Electrical Rigid Steel Conduit*

ASTM D396, *Standard for Specification for Fuel Oils*

ASTM E230/E230M, *Standard Specification and Temperature-Electromotive Force (emf) Tables for Standardized Thermocouples*

International Mechanical Code

NFPA 70, *National Electrical Code*

NFPA 211, *Standard for Chimneys, Fireplaces, Vents, and Solid Fuel Burning Appliances*

NFPA 90B, *Standard for Installation of Warm Air Heating and Air Conditioning Systems*

Standard Mechanical Code

UL 1004-3, *Thermally Protected Motors*

UL 2111, *Overheating Protection for Motors*

UL 353, *Limit Controls*

UL 723, *Tests for Surface Burning Characteristics of Building Materials*

UL 969, *Marking and Labeling Systems*

Uniform Mechanical Code

5 Glossary

5.1 For the purpose of this standard the following definitions apply.

5.2 AIR SHUTTER – An adjustable device for varying the size of the air inlet or inlets regulating primary air, secondary air, or both. It may be either manually or automatically operated.

5.3 APPLIANCE FLUE – The passages within the product that conduct the products of combustion (flue gases) through the product.

5.4 BURNER, OIL – A power-operated burner that prepares and delivers the oil and all or part of the air by mechanical process in controllable quantities for combustion.

5.5 CHIMNEY CONNECTOR – The pipe that connects a fuel-burning product to a chimney.

5.6 COMBUSTIBLE MATERIAL, COMBUSTIBLE PRODUCTS, NONCOMBUSTIBLE – These terms, as used in this standard, are defined in NFPA 211.

5.7 CONTROL, LIMIT – An automatic control responsive to changes in pressure or temperature and intended to limit the operation of the controlled equipment.

5.8 CONTROL, PRIMARY SAFETY – The automatic control relied upon to reduce the risk of discharge of oil at the burner in case of loss of ignition or loss of flame.

5.9 CONTROL, SAFETY – Any automatic control, such as a relay or switch, used in conjunction with other auxiliary equipment to form a safety control system that is relied upon to reduce the risk of fire, electric shock, or injury to persons.

5.10 CONTROL, SAFETY COMBUSTION – A primary control directly responsive to flame properties. Senses the presence of flame and causes fuel to be shut off in event of loss of flame.

5.11 CONTROL, THERMOSTATIC DAMPER – An automatic control responsive to changes in temperature. Usually acts through direct mechanical linkage to reduce or increase the supply of air needed for combustion, thereby regulating the combustion rate and limiting the operation of the product when the product is burning solid fuel.

5.12 CONVENIENCE RECEPTACLE – A contact device provided with permanently connected electrical conductors intended for quick and easy connection to a plug attached to a flexible electric cord.

5.13 DAMPER – A valve or plate that regulates draft or flow of flue gases or inlet combustion air. May be either manually or automatically operated.

5.14 DRAFT REGULATOR – A device that functions to maintain a desired draft in the product by automatically reducing the chimney draft to the desired value.

5.15 ELECTRICAL CIRCUITS:

a) High-Voltage Circuit – A circuit involving a potential of not more than 600 V and having circuit values in excess of those of a low-voltage circuit.

b) Low-Voltage Circuit – A circuit involving a potential of not more than 30 V alternating current (42.4 peak or direct current) and supplied by a NEC Class 2 transformer, or by a battery, or by a battery and fixed impedance, or by a transformer and fixed impedance each of which, as a unit, is either in compliance with requirements for a Class 2 transformer or is otherwise limited to a maximum output of 100 V-A. A circuit derived by connecting resistance in series with a high-voltage circuit as a means of limiting the voltage and current is not considered a low-voltage circuit.

c) Isolated Limited Secondary Circuit – A circuit of limited energy output derived from a isolated secondary winding of a transformer having a maximum capacity of 100 V-A and open-circuit secondary voltage rating not exceeding 1000 V.

5.16 FLOOR PROTECTOR (STOVE MAT) – The noncombustible material applied to the floor area underneath, in front of, and at the sides of the fuel charging area and underneath the chimney connector area of the product.

5.17 FUEL OIL – Any hydrocarbon oil defined by ASTM D396.

5.18 FURNACE, CENTRAL – A self-contained indirect-fired product supplying heated air through ducts to the space to be heated. Air is circulated either by means of a power-driven fan (a forced-air furnace) or by means of natural convection (a gravity furnace).

5.19 FURNACE, COMBINATION OIL-FIRED AND SOLID-FUEL-FIRED CENTRAL – A central furnace burning fuel oil and solid fuel either separately or simultaneously. The furnace makes use of either separate or common combustion chambers and flues for burning the two fuels.

5.20 FURNACE, SUPPLEMENTARY CENTRAL – A solid-fuel-burning product intended to be interconnected with a gas- or oil-fired forced-air central furnace by means of a common warm-air supply plenum in accordance with the manufacturer's instructions.

5.21 GRATE – A metal frame provided by the manufacturer for supporting the fuel within a furnace.

5.22 HEARTH – The floor area within the fire chamber of a furnace.

5.23 INDIRECT-FIRED VENTED PRODUCT – A product in which the products of combustion and the medium being heated (circulating air, for example) are segregated by the walls of the fire chamber and flues; it is provided with a flue collar to accommodate a chimney connector for conveying the products of combustion to the outdoors.

5.24 RADIATION SHIELD – A separate panel or separate panels interposed between heating surfaces and adjacent objects for the purpose of reducing heat transmission by radiation.

5.25 RADIATOR – Auxiliary heat transfer surfaces within the casing, connected between the combustion chamber and the flue collar.

5.26 SERVICING – The periodic tasks usually performed to operate and maintain a product, such as air, fuel, and pressure adjustments, cleaning of flues and chimney, lubrication, and resetting of controls. Repair and replacement of parts other than those expected to be renewed periodically, such as replacement of air filters, is not considered to be servicing. Some examples of servicing are:

- a) Cleaning or replacing nozzles;
- b) Setting ignition electrodes;
- c) Cleaning or replacing strainer or filter elements;
- d) Resetting safety control; and
- e) Replacing igniter cable.

CONSTRUCTION

6 General

6.1 A furnace shall be factory built as a complete assembly and shall include all the components necessary for its intended installation and operation. A furnace may be shipped as two or more major subassemblies.

6.2 Major subassemblies of a furnace are considered to be:

- a) The burner;
- b) The heat exchanger, including its base, combustion chamber, casing, and safety controls;

- c) The blower assembly, including its base, filters, and casing; and
- d) The blower motor, if not included as part of the blower assembly.

A wiring harness may be packaged with one of the major subassemblies.

6.3 A furnace shall be arranged in major subassemblies, if the furnace is not assembled by the manufacturer as a unit. Each subassembly shall be capable of assembly into the final assembly without the installer altering, cutting, drilling (except as indicated in [6.4](#)), threading, welding, or performing similar tasks. If the intended installation and operation of the furnace so requires, two or more subassemblies shall either:

- a) Be arranged and constructed so that they can be incorporated into the complete assembly only in the intended manner; or
- b) Be assembled, tested, and shipped from the factory as one element.

6.4 Cutting or drilling complies with the requirements of [6.3](#) if it is needed for either:

- a) The attachment of a return or supply plenum or an optional filter rack; or
- b) The provision of a return-air opening in the furnace casing. If a return-air opening is to be cut in the casing panel by the installer, either the necessary instructions and template shall be furnished with the furnace, or the corners of the opening shall be embossed in knockout form.

6.5 A radiation shield or baffle relied upon to reduce the risk of temperatures in excess of those intended shall:

- a) Be assembled as part of the furnace;
- b) Be part of a subassembly that must be attached to the furnace for its intended operation; or
- c) Be constructed so that the furnace cannot be assembled for operation without first attaching a required shield or baffle in its intended position.

6.6 Alteration or removal of a baffle, insulation, or radiation shield needed to reduce the risk of excessive temperatures shall not be required for any intended furnace installation.

6.7 The construction of a furnace shall permit the user to operate those parts requiring the user's attention or adjustment in anticipated usage.

6.8 An adjustable or movable part shall be provided with a locking device to secure it against unintended shifting.

6.9 A screw or bolt used to attach a part that may be detached for care or servicing of the product shall hold its position upon the application of the torque specified in [Table 6.1](#) after removal and replacement of the part.

**Table 6.1
Torque Requirements for Screws or Bolts**

American standard screw size		Torque		I.S.O. screw size	Torque	
No.	mm	Lbf-inch	N·m	mm	N·m	Lb-inch
–	–	–	–	4	1.6	14
8	4.2	18	2.0	4.5	2.6	23
10	4.8	30	3.4	5	4.2	37
Inch	(mm)	Lbf-inch	N·m	(mm)	N·m	Lb-inch
1/4	(6.4)	100	11.3	(6)	8.7	77
–	–	–	–	(7)	15.0	133
5/16	(7.9)	200	22.6	(8)	23.5	208
–	–	–	–	(9)	33.6	297
3/8	(9.5)	350	39.6	(10)	45.2	400
7/16	(11.1)	575	65.0	(12)	81.0	715
1/2	(12.7)	850	96.0	(14)	128.0	1130
9/16	(14.3)	1200	136.0	–	–	–
5/8	(15.9)	1600	181.0	(16)	185.0	1640

6.10 Any external door providing access to the combustion chamber of a furnace and intended for installation with a clearance of less than 24 inches (610 mm) from the face of the door or 48 inches (1219 mm) above the door shall be self-closing.

6.11 A furnace intended for installation in the cooled-air path, downstream from a cooling coil, shall comply with (a) – (d):

- a) All interior surfaces of the heat exchanger, combustion chamber (including its bottom), radiators, and flues shall resist corrosion by moisture.
- b) The firebox liner shall resist deterioration from wetting by condensation.
- c) Condensation shall not drip on burner parts or other parts vulnerable to corrosion if corrosion of any of the parts may cause a risk of fire, electric shock, or injury to persons.
- d) The heat exchanger and appliance flue shall not contain traps or pockets in which condensation may collect.

6.12 An oil burner shall be secured so that it will not twist, slide, or drop out of position.

6.13 A grate shall be used in a furnace intended to burn coal.

6.14 When a user's hand is withdrawn from a separable door handle (if provided) that is intended to be used either during solid-fuel loading and ash removal or with products requiring manual operation, the handle shall not remain in a position that allows temperatures on the handle to rise above those specified in [Table 57.1](#).

6.15 Provision shall be made for storing a separable handle on the furnace. When the handle is stored in its intended position, its temperature shall not exceed the appropriate temperature specified in [Table 57.1](#).

6.16 Fuel-loading and ash-removal doors shall not warp or misalign when the furnace is subjected to the tests specified in the Performance section of this standard if air leaking into the combustion chamber because of the warping or misalignment can result in a risk of overfiring or fire outside the furnace.

6.17 Fuel-loading and ash-removal doors shall close by gravity or shall be provided with a latch. Combination oil-fired and solid-fuel-fired furnace doors shall not open during delayed oil ignition unless it can be determined that particles of burning solid fuel cannot be expelled through the door opening by the force of the delayed oil ignition. See Delayed Oil Ignition Test, Section [60](#).

6.18 A combination oil-fired and solid-fuel-fired central furnace shall be provided with an interlock relied upon to reduce the risk of firing of the oil burner with either or both the solid-fuel loading door or the ash-removal door open, if this operation can result in the risk of fire, explosion, or injury to persons.

7 Accessibility for Servicing

7.1 A furnace shall be provided with means of access for cleaning of parts, such as internal heating surfaces in contact with combustion products, oil-inlet pipes, and oil strainers, without major dismantling of the furnace or removal of parts required to be factory-assembled.

7.2 With reference to the requirements of [7.1](#), the removal of access panels, burners, blowers, caps, plugs, and the like, permitting removal and replacement of parts for servicing, and the detachment of the chimney connector are not considered major dismantling.

7.3 All burners, controls, and safety devices shall be accessible for cleaning, inspection, repair, and replacement when the furnace is installed as intended by the manufacturer. Parts in the assembly removable for servicing shall be arranged so that their restoration, following removal, will not necessitate their realignment to secure their intended relationship with other parts of the assembly. Special facilities required for servicing to be performed by the operator shall accompany the furnace as supplied by the user.

8 Protection of Users and Service Personnel

8.1 An uninsulated, high-voltage live part or a moving part that creates a risk of injury to persons shall be located, guarded, or enclosed so as to reduce the risk of unintended contact by personnel performing service functions that may have to be performed while the equipment is energized.

8.2 Service functions that may have to be performed while the equipment is energized include:

- a) Adjusting the setting of temperature controls that do or do not have marked dial settings;
- b) Resetting a control trip mechanism;
- c) Operating manual switches; and
- d) Adjusting air-flow dampers.

A factory-set and -sealed control is not considered adjustable.

8.3 The requirements of [8.1](#) are not applicable to mechanical service functions not anticipated to be performed while the equipment is energized. Such functions include adjusting or replacing belts and cleaning and replacing strainers and oil filters.

8.4 Adjustable or resettable electrical control or manual switching devices may be located or oriented with respect to uninsulated high-voltage live parts so that manipulation of the mechanism for adjustment,

resetting, or operation can be accomplished in the intended direction of access if uninsulated, high-voltage live parts or moving parts involving a risk of injury to persons are:

- a) Not located in front of or in the direction of access to the mechanism; and
- b) Are not located within 6 inches (152 mm) of the mechanism, whether the parts are positioned on any side of the mechanism or whether they are behind it, unless they are guarded.

8.5 The location and mounting of an electrical control component relative to other components and grounded metal parts shall not subject service personnel to risk of electric shock from adjacent uninsulated live parts or the risk of injury from adjacent moving parts if components need to be reached while it is energized.

Exception: This requirement does not apply when service personnel make voltage measurements using jacks or terminals specifically intended for the purpose.

8.6 Accessibility to each compartment and protection of persons from the risk of electric shock and contact with moving parts that can cause injury may be obtained by mounting the control components in an assembly so that unimpeded access is provided to each compartment through an access cover or panel in the outer cabinet and through the cover of the control assembly enclosure described in (a) – (e). See [Figure 8.1](#).

- a) The components shall be located with respect to the access opening in the outer cabinet so that the farthest component in the control assembly is not more than 14 inches (356 mm) from the plane of the access opening.
- b) Uninsulated live parts that lie outside the control assembly's projected clear space (except for live parts within a control panel) or unguarded moving parts that create a risk of injury to persons shall be located not closer than 6 inches (152 mm) to any side of the access area. The projected clear space is considered to be bounded on the sides by the projection of the smallest rectangular perimeter that can surround the outside edge of the components or control enclosure, when such an enclosure is provided. The access area is considered to be bounded on the sides by the projection of the perimeter of the access opening in the outer cabinet to the closest rectangular perimeter surrounding the outside edge of the component or control enclosure.
- c) The volume generated by the projected clear space of the control assembly to the access opening in the outer cabinet (within the access area) shall be free of obstructions, including wiring.
- d) Access to the components in the control assembly shall not be impeded in the direction of access by other components or by wiring in this assembly.
- e) Extractor-type fuseholders and snap switches mounted through the control assembly enclosure shall be located so that:
 - 1) There is unimpeded access to these components through the access opening in the outer cabinet; and
 - 2) The components are not immediately adjacent to uninsulated live parts outside the control assembly enclosure, unless these parts are guarded. See [40.4](#).