



UL 730

STANDARD FOR SAFETY

Oil-Fired Wall Furnaces

[ULNORM.COM](https://www.ulnorm.com) : Click to view the full PDF of UL 730 2022

[ULNORM.COM](https://www.ulnorm.com) : Click to view the full PDF of UL 730 2022

UL Standard for Safety for Oil-Fired Wall Furnaces, UL 730

Fifth Edition, Dated August 29, 2003

Summary of Topics

This revision of UL 730 dated August 19, 2022 is being issued to remove the ANSI logo and approval from the title page. No other changes have been made.

Text that has been changed in any manner or impacted by UL's electronic publishing system is marked with a vertical line in the margin.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of UL.

UL provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will UL be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if UL or an authorized UL representative has been advised of the possibility of such damage. In no event shall UL's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold UL harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

ULNORM.COM : Click to view the full PDF of UL 730 2003

No Text on This Page

[ULNORM.COM](https://ulnorm.com) : Click to view the full PDF of UL 730 2022

AUGUST 29, 2003

(Title Page Reprinted: August 19, 2022)

1

UL 730

Standard for Oil-Fired Wall Furnaces

First Edition – August, 1955

Second Edition – September, 1974

Third Edition – June, 1987

Fourth Edition – December, 1994

Fifth Edition

August 29, 2003

This UL Standard for Safety consists of the Fifth Edition including revisions through August 19, 2022.

Comments or proposals for revisions on any part of the Standard may be submitted to UL at any time. Proposals should be submitted via a Proposal Request in UL's On-Line Collaborative Standards Development System (CSDS) at <https://csds.ul.com>.

UL's Standards for Safety are copyrighted by UL. Neither a printed nor electronic copy of a Standard should be altered in any way. All of UL's Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of UL.

COPYRIGHT © 2022 UNDERWRITERS LABORATORIES INC.

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 730 2022

CONTENTS

INTRODUCTION

1	Scope	5
2	General	5
3	Glossary	5
3A	Undated References	9
4	Components	9

CONSTRUCTION – MECHANICAL

5	Assembly	9
6	Servicing	11
	6.1 General	11
	6.2 Moving parts	12
7	Disposal of Combustion Products	12
8	Casing	13
9	Radiation Shields	13
10	Materials in Air Handling Compartment	13
11	Air Filter	14
12	Combustion Chamber	14
13	Radiator	14
14	Heating Surface Joints	15
15	Baffles	15
16	Flue Collar	15
17	Damper and Draft Regulator	16

CONSTRUCTION – ELECTRICAL

18	Controls	16
	18.1 Application	16
	18.2 Limit control	16
	18.3 Primary safety control	17
19	Field Wiring	17
	19.1 General	17
	19.2 Leads and terminals	18
20	Internal Wiring	19
	20.1 General	19
	20.2 Methods	20
	20.3 Short circuit protection	23
21	Separation of Circuits	23
22	Bonding for Grounding	24
23	Servicing and Adjustment	27
24	Electrical Components	28
25	Mounting of Electrical Components	28
26	Electrical Enclosures	28
	26.1 General	28
	26.2 Doors and covers	32
27	Motors and Motor Overcurrent (Overload) Protection	33
28	Switches and Controllers	37
29	Capacitors	37
30	Insulating Material	38
31	Spacings – High Voltage Circuits	38
32	Spacings – Low-Voltage Circuits	39

33	Accessibility of Uninsulated Live Parts, Film-Coated Wire, and Moving Parts	40
----	---	----

PERFORMANCE

34	General	45
35	Test Installation – Built-In Style Furnaces	45
	35.1 Enclosure	45
	35.2 Venting	46
36	Test Installation – Extended Style Furnaces	48
	36.1 Enclosure	48
	36.2 Chimney connector	50
37	Instrumentation	54
	37.1 Draft	54
	37.2 Fuel input	54
	37.3 Power measurement	54
	37.4 Speed measurement	54
	37.5 Temperature measurement	54
38	Initial Test Conditions	59
	38.1 General	59
	38.2 Furnace equipped with mechanical atomizing burner	60
	38.3 Furnace equipped with vaporizing burner	60
39	Combustion Test – Burner and Furnace	60
40	Operation Tests	61
41	Limit Control Cutout Test	61
42	Continuity of Operation Test	61
43	Temperature Tests	62
	43.1 General	62
44	Continuous Operation Temperatures	65
45	Blocked Register Test	66
46	Blocked Inlet Test	67
47	Fan Failure Test	67
48	Stalled Fan Motor Test	68
49	Seepage and Burnoff Test	68
50	Short Circuit Test	69
51	Dielectric Voltage Withstand Test	71
52	Flammability Test	71

MANUFACTURING AND PRODUCTION TESTS

53	General	72
----	---------------	----

MARKING

54	General	73
----	---------------	----

INSTRUCTIONS

55	Operating and Installation Instructions	75
----	---	----

APPENDIX A

	Standards for Components	76
--	--------------------------------	----

INTRODUCTION

1 Scope

1.1 These requirements apply to oil-fired, vented, fan-type wall furnaces. Requirements for the installation and use of oil-burning equipment are included in the Standard for the Installation of Oil-Burning Equipment, NFPA 31.

1.2 A product that contains features, characteristics, components, materials, or systems new or different from those covered by the requirements in this standard, and that involves a risk of fire or of electric shock or injury to persons shall be evaluated using appropriate additional component and end-product requirements to maintain the level of safety as originally anticipated by the intent of this standard. A product whose features, characteristics, components, materials, or systems conflict with specific requirements or provisions of this standard does not comply with this standard. Revision of requirements shall be proposed and adopted in conformance with the methods employed for development, revision, and implementation of this standard.

2 General

2.1 Values stated without parentheses are the requirement. Values in parentheses are explanatory or approximate information.

3 Glossary

3.1 For the purpose of this standard the following definitions apply.

3.2 AIR SHUTTER – An adjustable device for varying the size of the air inlet or inlets regulating primary or secondary air.

3.3 ANTIFLOODING DEVICE – A primary safety control which causes the fuel flow to be shut off upon a rise in fuel level or upon receiving excess fuel, and which operates before the hazardous discharge of fuel can occur.

3.4 APPLIANCE FLUE – The flue passages within the appliance.

3.5 AUTOMATICALLY LIGHTED APPLIANCE – An appliance in which fuel to the main burner is normally turned on and ignited automatically.

3.6 BAFFLE – An object placed in an appliance to direct the flow of air or flue gases.

3.7 BASE – The main supporting frame or structure of the wall furnace, exclusive of legs.

3.8 BURNER, MECHANICAL ATOMIZING TYPE – A power operated burner which prepares and delivers the oil and all or part of the air by mechanical process in controllable quantities for combustion. Some examples are air atomizing, high and low pressure atomizing, horizontal rotary, vertical rotary atomizing, and vertical rotary wall flame burners.

3.9 BURNER, MECHANICAL DRAFT TYPE – A burner which includes a power driven fan, blower, or other mechanism as the principal means for supplying air for combustion.

3.10 BURNER, NATURAL DRAFT TYPE – A burner which depends principally upon the natural draft created in the flue to induce into the burner the air required for combustion.

- 3.11 BURNER, VAPORIZING TYPE – A burner consisting of an oil vaporizing bowl or other receptacle to which liquid fuel may be fed in controllable quantities; the heat of combustion being used to vaporize the fuel, with provision for admitting air and mixing it with the oil vapor in combustible proportions.
- 3.12 CASING – An enclosure forming the outside of the appliance, no parts of which are likely to be subjected to intense heat.
- 3.13 CENTRAL HEATING APPLIANCE – A stationary indirect-fired vented appliance comprising the following classes: boilers, central furnaces, floor furnaces, and wall furnaces. A floor mounted unit heater to be connected to a duct system is categorized also as a central heating appliance.
- 3.14 CHIMNEY CONNECTOR – The pipe which connects a solid or liquid fuel burning appliance to a chimney.
- 3.15 COMBUSTIBLE MATERIAL – Combustible material as pertaining to materials adjacent to or in contact with heat producing appliances, chimney connectors and vent connectors, refers to material made of or surfaced with wood, compressed paper, plant fibers, or other material that will ignite and burn. Such material shall be considered as combustible even though flame-proofed, fire-retardant treated, or plastered.
- 3.16 COMBUSTION – The rapid oxidation of fuel accompanied by the production of heat, or heat and light. Complete combustion of a fuel is possible only in the presence of an adequate supply of oxygen.
- 3.17 COMBUSTION CHAMBER – The portion of an appliance within which combustion occurs.
- 3.18 COMBUSTION (FLAME) SAFEGUARD – A safety combustion control.
- 3.19 CONSTANT LEVEL VALVE – A device for maintaining within a reservoir a constant level of fuel for delivery to the burner.
- 3.20 CONTROL – A device intended to regulate the fuel, air, water, or electrical supply to the controlled equipment. It may be automatic, semiautomatic, or manual.
- 3.21 CONTROL, LIMIT – An automatic safety control, responsive to changes in liquid level, pressure, or temperature, for limiting the operation of the controlled equipment.
- 3.22 CONTROL, SAFETY – Automatic controls, including relays, switches, and other auxiliary equipment used in conjunction therewith to form a safety control system, which are intended to prevent unsafe operation of the controlled equipment.
- 3.23 CONTROL, PRIMARY SAFETY – The automatic safety control intended to prevent abnormal discharge of oil at the burner in case of ignition failure or flame failure.
- 3.24 CONTROL, SAFETY COMBUSTION – A primary safety control responsive directly to flame properties, sensing the presence of flame and causing fuel to be shut off in event of flame failure.
- 3.25 DAMPER – A valve or plate for regulating draft or flow of flue gases. A damper is generally considered as being located on the downstream side of the combustion chamber, usually in a flue passage of the appliance or in the chimney connector.
- 3.26 DAMPER, AUTOMATICALLY OPERATED – A damper operated by an automatic control.

3.27 DAMPER, MANUALLY OPERATED – An adjustable damper manually set and locked in the desired position.

3.28 DRAFT REGULATOR – A device which functions to maintain a desired draft in the appliance by automatically reducing the chimney draft to the desired value.

3.29 ELECTRICAL CIRCUITS:

a) High-Voltage Circuit – A circuit involving a potential of not more than 600 volts and having circuit characteristics in excess of those of a low-voltage circuit.

b) Low-Voltage Circuit – A circuit involving a potential of not more than 30 volts alternating current (42.4 peak or direct current) and supplied by a primary battery or by a standard Class 2 transformer or other suitable transforming device, or by a suitable combination of transformer and fixed impedance having output characteristics in compliance with what is required for a Class 2 transformer. A circuit derived from a source of supply classified as a high-voltage circuit, by connecting resistance in series with the supply circuit as a means of limiting the voltage and current, is not considered to be a low-voltage circuit.

c) Safety Control Circuit – A circuit involving one or more safety controls.

3.30 EXCESS AIR – Air which passes through the combustion area and the appliance flues in excess of that which is theoretically required for complete combustion.

3.31 FLUE – The general term for the conduit or passageway through which flue gases pass from the combustion chamber to the outer air.

3.32 FLUE COLLAR – That portion of an appliance intended for attachment of the chimney or vent connector.

3.33 FLUE GASES – Combustion products and excess air.

3.34 FUEL OIL – Any hydrocarbon oil as defined by the Standard for Specification for Fuel Oils, ANSI/ASTM D396.

3.35 HEAT EXCHANGER, DIRECT – A heat exchanger in which heat generated in the combustion chamber of the appliance is transferred direct through walls of the appliance to the heating medium, such as air, steam, or water, and held in close contact with the combustion chamber walls. It is a self-contained combustion and heat transfer device, hence a direct heat transfer device.

3.36 HEAT EXCHANGER, INDIRECT – A heat exchanger which encloses or contains a heating medium, such as air, steam, or water, the heat from which is transferred to another heating medium separately contained in close contact with or directed through the heat exchanger. It is an indirect heat transfer device.

3.37 HEATING SURFACES – All surfaces which transmit heat directly from flame or flue gases to the medium to be heated.

3.38 INDIRECT FIRED APPLIANCE – An appliance designed so that combustion products or flue gases are not mixed in the appliance with the medium to be heated; and provided with a flue collar.

3.39 LIMIT CONTROL – See Control, Limit – [3.21](#).

3.40 LINER – See Radiation Shield – [3.46](#).

3.41 MANUALLY LIGHTED APPLIANCE – An appliance in which fuel to the main burner is turned on only by hand and ignited under supervision.

3.42 NORMAL CARE – The periodic tasks usually performed to operate and maintain an appliance, such as air, fuel, pressure, and temperature regulation, cleaning, lubrication, resetting of controls, and the like. Repair and replacement of parts other than those expected to be renewed periodically is not considered to be normal care. Some examples of normal care are:

- a) Cleaning or replacing nozzles, atomizers, and pilots.
- b) Setting ignition electrodes.
- c) Cleaning strainers or replacing strainer or filter elements.
- d) Resetting safety control.
- e) Replacing igniter cable.

3.43 OIL-FIRED WALL FURNACE – A wall furnace equipped with one or more oil burners, and all the necessary safety controls, electrical equipment as needed, and related equipment, manufactured for assembly as a complete unit. This definition does not include oil stoves.

3.44 PILOT – A flame which is utilized to ignite the fuel at the main burner or burners.

3.45 PRIMARY AIR – The air introduced into a burner and which mixes with the fuel before it reaches the ignition zone.

3.46 RADIATION SHIELD – A separate panel or panels interposed between heating surfaces and adjacent objects to reduce heat transmission by radiation.

3.47 RADIATOR – Auxiliary heat transfer surfaces within the casing, connected between the combustion chamber and the flue collar.

3.48 READILY ACCESSIBLE – Capable of being reached easily and quickly for operation, adjustment, and inspection.

3.49 SAFETY CONTROL – See Control, Safety – [3.22](#).

3.50 SECONDARY AIR – The air externally supplied to the flame at or beyond the point of ignition.

3.51 SPECIAL PARTS AND TOOLS – Those parts and tools that are not available on the open retail market.

3.52 THERMOSTAT – An automatic control actuated by temperature change to maintain temperatures between predetermined limits.

3.53 VALVE MANUAL OIL SHUT-OFF – A manually operated valve in the oil line for the purpose of completely turning on or shutting off the oil supply to the burner.

3.54 VALVE, OIL CONTROL – An automatically or manually operated device consisting essentially of an oil valve for controlling the fuel supply to a burner:

- a) Metering (Regulating) Valve – An oil control valve for regulating burner input.

b) Safety Valve – A normally closed valve of the ON and OFF type, without any bypass to the burner, that is actuated by a safety control or by an emergency device.

3.55 VENTED APPLIANCE – An indirect fired appliance provided with a flue collar to accommodate a flue pipe for conveying flue gases to the outer air.

3.56 WALL FURNACE – A self-contained indirect-fired appliance intended for incorporation in, insertion into, or permanent attachment to a wall or partition, and furnishing heated air circulated by gravity or by a fan directly into the space to be heated through openings in the casing.

3A Undated References

3A.1 Any undated reference to a code or standard appearing in the requirements of this standard shall be interpreted as referring to the latest edition of that code or standard.

4 Components

4.1 Except as indicated in [4.2](#), a component of a product covered by this standard shall comply with the requirements for that component. See Appendix [A](#) for a list of standards covering components generally used in the products covered by this standard.

4.2 A component is not required to comply with a specific requirement that:

- a) Involves a feature or characteristic not required in the application of the component in the product covered by this standard, or
- b) Is superseded by a requirement in this standard.

4.3 A component shall be used in accordance with its rating established for the intended conditions of use.

4.4 Specific components are incomplete in construction features or restricted in performance capabilities. Such components are intended for use only under limited conditions, such as certain temperatures not exceeding specified limits, and shall be used only under those specific conditions.

CONSTRUCTION – MECHANICAL

5 Assembly

5.1 A wall furnace shall be factory built as a group assembly and shall include all the essential components necessary for its normal function when installed as intended. A wall furnace may be shipped as two or more major subassemblies.

5.2 A wall furnace, if not assembled by the manufacturer as a unit, shall be arranged in major subassemblies. Each subassembly shall be capable of being incorporated readily into the final assembly without requiring alteration, cutting, drilling (except to the extent indicated in [5.3](#)), threading, welding, or similar tasks by the installer. Two or more subassemblies, which must bear a definite relationship to each other for the proper and safe installation or operation of the furnace, shall be arranged and constructed to permit them to be incorporated into the complete assembly only in the correct relationship with each other, without need for alteration or alignment, or such subassemblies shall be assembled, tested, and shipped from the factory as one element.

5.3 To be in accordance with [5.2](#), major subassemblies of a wall furnace are deemed to be the:

- a) Burner;
- b) Heat exchanger, including its base, combustion chamber, casing, and safety controls;
- c) Blower assembly, including the base, filters, and casing; and
- d) Blower motor if not included as part of the blower assembly.

A wiring harness may be packaged with one of the major subassemblies.

5.4 A radiation shield or baffle employed to prevent excessive temperature shall be:

- a) Assembled as part of the furnace;
- b) Part of a subassembly that must be attached to the furnace for its normal operation; or
- c) Such that the furnace cannot be assembled for operation without first attaching a required shield or baffle in its proper position.

5.5 The design of a wall furnace shall be such that, for any normal installation, the alteration or removal of a baffle, insulation, or a radiation shield needed to prevent unsafe temperatures is not required.

5.6 A wall furnace shall afford convenient operation by the user of those parts requiring attention or manipulation by him in normal usage.

5.7 Adjustable or movable parts shall be provided with locking devices to prevent accidental shifting.

5.8 Screws or bolts used to attach parts which are detached for normal care or servicing of the appliance shall be capable of holding upon the application of the torques indicated in [Table 5.1](#) after removal and replacement.

Table 5.1
Maximum torque requirements for screws

Screw size (mm)		Torque,	
		pound-inches	(N·m)
No. 8	(4.2)	20	(2.3)
No. 10	(4.8)	25	(2.8)
1/4 inch	(6.4)	100	(11.3)
5/16 inch	(7.9)	200	(22.6)
3/8 inch	(9.5)	350	(39.5)
7/16 inch	(11.1)	550	(62.1)
1/2 inch	(12.7)	800	(90.3)
9/16 inch	(14.3)	1200	(135.5)

5.9 A wall furnace shall be such that no portion of the products of combustion nor any portion of the heated circulating air or air from the space being heated will be discharged into spaces within walls, floor, or ceiling. Openings in the jacket, top, or sides, through which the chimney connector extends, shall be sufficiently close fitting to comply with this requirement.

5.10 A wall furnace shall be constructed to provide a constant circulation of heated air at all times during normal operations.

5.11 A wall furnace with a single warm air register shall not be equipped with a shutter to restrict the flow of warm air from the heater.

5.12 A wall furnace having more than one warm air register, when equipped with a shutter, shall be such that at least one warm air register will be open at any position of the shutter.

5.13 The bottom of the heater shall provide an oil-tight pan with an upturned flange not less than 1/2 inch (12.7 mm) high around the periphery and around any openings through the pan. All oil handling parts, including the fuel supply line connection, shall be directly above the pan.

5.14 The construction of a wall furnace shall provide for maintaining the minimum clearance required between the bottom, sides, and top of the furnace and concealed surfaces of the wall or partition in which or to which the furnace is to be installed. Spacers shall be of such strength and bearing surface as to maintain required clearance from building material.

5.15 The requirement of [5.14](#) does not apply to unconcealed portions of a furnace extending beyond the wall or partition into a readily accessible space such as an alcove, closet, or room. The clearance from such portions of the furnace to combustible construction may be as specified in integral inches by the manufacturer in the instructions for installation and as marked on the unit. See [54.1](#).

5.16 If the chimney connector is located within the wall or partition structure when the furnace is installed as intended, the furnace shall be designed for direct connection to a chimney or venting system when the furnace is placed directly adjacent to or beneath the chimney or venting system. Any special connection or extension required shall be provided as part of the furnace.

5.17 Any external door providing access into the combustion chamber of a wall furnace shall be self-closing.

5.18 A burner shall be secured so it will not twist, slide, or drop out of position.

5.19 A wall furnace equipped with an anti-flooding device shall be such that, when the furnace is level, the minimum distance between the intended maximum normal oil level maintained by the oil control device and the level of the lowest point at which overflow may occur is not less than 3/4 inch (19.1 mm).

6 Servicing

6.1 General

6.1.1 A wall furnace shall be built to allow cleaning of parts such as interior surfaces of vaporizing burners, heating surfaces in contact with combustion products, oil inlet pipes, and oil strainers, without major dismantling of the wall furnace or removal of parts required by [5.2](#) to be factory assembled.

6.1.2 The removal of access panels, burners, blowers, caps, plugs, and the like intended to permit ready removal and replacement for servicing, are not considered major dismantling as defined by [6.1.1](#).

6.1.3 Sufficient and reasonable accessibility shall be afforded for cleaning, inspection, repair, and replacement of all burners, controls, and safety devices when the wall furnace is installed as recommended by the manufacturer. The disposition of parts in the assembly removed for normal care shall be such that their restoration, following removal, will not necessitate their realignment to secure their proper relationship with other parts of the assembly. Special facilities required for normal care to be done by the operator shall accompany the wall furnace to the user.

6.1.4 The requirements of [33.1](#) are not applicable to mechanical service functions that are not intended to be performed while the equipment is energized.

6.2 Moving parts

6.2.1 Moving parts such as fan blades, blower wheels, pulleys, belts, and the like, which may cause injury shall be enclosed or guarded.

6.2.2 If the removal of doors, panels, or shields will expose such moving parts:

- a) The opening or removal of the door, panel or shield shall require the use of tools; or
- b) An interlocking device shall shut off the mechanism; or
- c) A warning marking shall be displayed which reads essentially as follows:

DANGER – To Avoid Injury From Moving Parts, Shut Off The (Equipment) Before (Removing-Opening) This (Cover-Door).

6.2.3 The distance from an opening in a required guard or enclosure to the moving part mentioned in [6.2.2](#) shall be in accordance with [Table 6.1](#), but the minor dimension of the opening shall not in any case exceed 3 inches (76.2 mm). For an opening having a minor dimension intermediate between two of the values included in the table, the distance from the opening to the moving part shall be not less than that found by appropriate interpolation between the corresponding values in the right-hand column of the table. The minor dimension of the opening is determined by the largest hemispherically tipped cylindrical probe that can be inserted through the opening with a force of 5 pounds (22.5 N).

Table 6.1
Dimensions of openings

Minor Dimensions of Opening,		Minimum Distance from Opening to Moving Part,	
Inches ^a	(mm)	Inches	(mm)
1/4	(6.4)	1/2	(12.7)
3/8	(9.5)	1-1/2	(38.1)
1/2	(12.7)	2-1/2	(63.5)
3/4	(19.1)	4-1/2	(114)
1	(25.4)	6-1/2	(165)
1-1/2	(38.1)	10-1/2	(267)
2	(50.8)	14-1/2	(369)
Over 2 Inches (over 50.8)		30	(762)

^a Openings less than 1/4 inch (6.4 mm) are not to be considered.

6.2.4 A moving part is not to be considered when judging compliance with [33.1](#) and [6.2.2](#) if the part is unlikely to be contacted through the opening because of fixed components, including baffles.

7 Disposal of Combustion Products

7.1 The construction of a wall furnace shall not allow the products of combustion to become mixed with the circulating air.